

Quick Release Single Chamber ICE Bladder Model: <u>COMP-QRB-15/20/30</u>

Rev. A

Operation Manual



Compcooler Technology Jan. 2021



COMPCOOLER Introduction:

Compcooler Technology specializes in working for personal cooling & heating systems for harsh conditions. Compcooler has established its resume as a manufacturer for Military, Electronic, Medical cooling equipment. The employees at Compcooler's state of the art manufacturing facility have been producing liquid heating & cooling systems over 15 years. Quality system: ISO9001 and AS9100 registered facility. Certifications for major items: CE, FCC, UL, PSE, CB, FDA.

Product Categories

- 1. Personal ICE Water Circulation Systems
- 2. Micro Refrigeration Chiller Units
- 3. Liquid Heating & Cooling Chiller
- 4. Liquid Cooling & Heating Garment
- 5. Industrial Chiller Unit Module
- 6. Customized Cooling Systems

Certifications for major items



Quality System for facility





BACKGROUND OF PERSONAL COOLING SYSTEM

In conditions of extreme heat, people may be at risk of heat stress where body under stress from overheating. Heat stress is not only a serious condition for workers, but it can result in occupational illnesses and injuries, heat related discomforts and illnesses include heat exhaustion, heat cramps, heat rash or even heat stroke. Symptoms can range from profuse sweating to dizziness, cessation of sweating and collapse. At greatest risk of heat stroke are the elderly, children and people with medical conditions, however, even young and healthy individuals can succumb to heat if they participate in strenuous physical activities during hot weather. It will need immediate action to cool the person until help arrives.

LIQUID CIRCULATION COOLING SYSTEM

Liquid circulation cooling system is an active cooling solution, it can cool the body temperature fast to decrease incidence of thermal stress and heat stroke while increase comfort, safety, focus and endurance. Liquid circulation system includes a liquid circulation unit and a cooling garment. Mini pump circulates cold water from chiller or ICE bladder to cooling channels embedded on the cooling garment, and continuously flow around the body, it will keep the user's body temperature at a comfort and safety range.

BENEFITS OF LIQUID COOLING SYSTEM

Reduction in body core temperature, increased duration. Reduction in skin temperature, decrease in hydration need Reduction in heart rate, improve mental acuity Reduction in sweat rate, maintain physical performance

COMPCOOLER Personal ICE Water Circulation Cooling System (PICS)

PICS includes a liquid circulation unit and liquid cooling garment. Mini pump circulates the cold ICE water from bladder to micro-tubing cooling channel embedded on the liner of garment, it continuously flows around the body to reduce body core temperature and keep user at a comfortable cool range in hot conditions.

Detachable Bladder: 1.5L, 2.0L, 3.0L and 4.0L (Hydration) Cooler Unit: 6L, 25L Cooler Pump Control Unit: ON/OFF mode: cold water circulation only Flow control mode: 3 levels water flow control Temp control mode: precise temp control for circulation liquid Liquid Temperature range: 2°C-10°C (36 °F -50 °F)

Cooling time: 1-3 hours for 1.5L frozen bladder

3-6 hours for 3.0L frozen bladder

4-8 hours for 6L ICE Cooler

8-12 hours for 25L ICE Cooler

Operation Ambient: 10°C-65°C (36 °F -148 °F)



Quick Release Single Chamber ICE Bladder Model: <u>COMP-QRB-30</u>

Introduction:

COMPCOOLER quick released single chamber ICE Bladder was designed for personal ICE water cooling systems, user may freeze the bladder or start quick cooling by ice cubes.



Bladder Size and Applications

• 1.5L/2.0L Single Chamber ICE Bladder: Waistpack ICE Water Cooling Systems

• 3.0L Single Chamber ICE Bladder: Backpack ICE Water Cooling Systems UniVest ICE Water Cooling Systems

Cooling Features:

- ICE Block Water Circulation
- ICE Cubes Water Circulation



Preparation: Unit Connection and Primary Circulation



Bladder Connection:

Fill water into Roll-Top, do not fill above overfill line. Connect the bladder Outlet/Inlet with backpack unit.

Checking: bladder no leaks, quick fittings connection is fine,

Vest Connection:

Connect backpack unit with cooling vest, once you hear a click, it's in position.

Checking: Vest no leaks, quick fittings connection is fine.

Start circulation:

Press On/Off switch, Pump circulates water from bladder into micro tubing cooling channels of cooling vest, then flow back to bladder. User may see the water flow back to bladder from Inlet fitting.

Checking: Battery works fine, pump works fine.



Mode A Cold Water Circulation Temp Range: 2°C -5°C (36°F-41°F) Frozen Bladder

Step I : Bladder Freeze

Fill water into Roll-Top to Fill Line, do not fill above the Overfill Line. Water must be below fill line to create an air packet. After freezing, the air bubble fills with circulation water for pump.

Step II: Circulation Water After bladder is frozen, fill small amount circulation water into the roll top.

Step III: Bladder Connection Connect the frozen bladder Outlet/Inlet quick fitting with backpack unit

Step IV: Start circulation Press On/Off Switch or temp controller, pump starts to circulation, user may feel the cooling in 60 seconds

Cooling Performance

Cooling time: 1-2 hours by 1.5L Bladder 2-4 hours by 3.0L Bladder Temp Range: 2°⊂ -5°⊂ (36°F-41°F) Hydration: Not Available





<u> Mode B :</u>

Quick Cold Water Circulation

<u>Temp Range: 4°C -6°C (39°F-43°F)</u> ICE Cubes

Step I : Bladder Freeze Fill ICE Cubes to full from Roll-Top.

Step II: Circulation Water Fill small amount circulation water from Roll-Top

Step III: Bladder Connection Connect the bladder Outlet/Inlet quick fitting with backpack unit

Step IV: Start circulation Press On/Off Switch or temp controller, pump starts to circulation, user may feel the cooling in 60 seconds

Cooling Performance

Cooling time: 0.5-1.5hours by 1.5L Bladder 1-2 hours by 3.0L Bladder Temp Range: 4°⊂ -6°⊂ (39°F-43°F) Hydration: Not Available



Safety:

It is important to become thoroughly familiar with the manual and operating characteristics of the unit. It is the owner's responsibility to assure proper operator training, installation, operation and maintenance of the unit. Observe all warning can result in injury to the operator and severe mechanical damage to the unit.

Warranty:

Compcooler Warrants to the original Purchaser that products sold shall be free from defects material and workmanship for warranty period not exceed one year from the date of shipment. Compcooler agrees to correct for the original user of this product, either by repair, or at the manufacturer's election by replacement. This warranty shall not apply if the defect or malfunction was caused by accident, neglect, unreasonable use, improper service, or other causes not arising out of defects in material or workmanship. The manufacturer's sole obligation under this warranty is limited to the repair or replacement of a defective product and shall not in any event be liable for any incidental or consequential damages of any kind resulting from use or possession of this product.



Personal Thermal Technology, Keep you body cool and comfortable in harsh conditions!