

Function Description

- Dual functionality: Combination of USB charging port and outlets
- Wide Space & Double Stability
- Surge Protection with Indicator Lights
- With overload protected
- Operating environment: for indoor use only



Input & Output Appearance



Ratings & Approval

2X  8X  1X 

AC Input: 125VAC 60Hz

AC Output: 15A 1875W

USB Charging Ports: 2 USB-A+1 USB-C

Combined USB Output Rating: 5V 3.4A

Individual USB Output Rating: 5V 2.4A

Surge Joule Rating: 800J



Packing



Product Measurement (inch): 4.41×2.44×4.53

Product Weight (lb): 0.49

Unit Package Measurements (inch): 4.41×2.44×4.53

Unit Package Weight (lb): 0.56

Master Carton Measurements (inch): 22.44×13.90×10.24

Master Carton Weight (lbs): 29.75

Master Carton Quantity: 50 PCS

Master Carton Cube (cu.ft): 1.85

BN-LINK INC.

11701 6th Street, Rancho Cucamonga, CA 91730

Customer Service Assistance: 1.909.592.1881

E-mail: support@bn-link.com

[Http://www.bn-link.com](http://www.bn-link.com)

Hours: 9AM - 5PM PST, Mon - Fri

Designed in California Made in China