



## ULURU LED Oyster

The Uluru surface mounted LED ceiling or wall lights feature a modern trimless design great for updating older traditional Oysters found in homes and commercial areas. Being only 38mm high it blends in with the ceiling and gives a uniform light, the 25W version is dimmable and all sizes are IP54 so you can install it inside or outside.



### Specifications

Wattage:	12W/18W/25W/30W
Beam Angle:	115°
Dimensions:	12W: D250xH40mm 18W: D300xH38mm 25W: D300xH38mm 36W: D400xH46mm
Driver:	Built-in constant current LED driver, Built-in trailing edge dimming LED driver for 25W only
Power Factor:	>0.95
Input Voltage:	240V
Electrical Classification:	Class II
IP Rating:	IP54
IK Rating:	IK07
Mounting:	Surface mounted
Material:	ABS + PC body, and high transmittance PMMA diffuser
Colour:	Powder coated white color
Warranty:	5 years residential 3 years commercial



### Dimensions



Size	Ø	H
12W	250	40
18W	300	38
25W	300	38
30W	400	46

### Model Comparison

Model No.	Power (W)	CCT (K)	Lumen (lm)	DIM
UL-250-12W-TC-WH	12	3000	1050	No
		4000	1150	
		5700	1135	
UL-300-18W-TC-WH	18	3000	1500	No
		4000	1600	
		5700	1550	
UL-300-25W-TC-DIM-WH	25	3000	2100	Yes
		4000	2200	
		5700	2200	
UL-400-30W-TC-WH	30	3000	2500	No
		4000	2700	
		5700	2600	

### LED Information

LED Chip Type:	SMD LED chips
CCT:	3000K/4000K/5700K
Lumen:	12W: 1050/1150/1135 lm 18W: 1500/1600/1550 lm 25W: 2100/2200/2200 lm 30W: 2500/2700/2600 lm
Efficiency	>90 lm/W
CRI Rating:	>80
Life Span:	50,000Hrs