

ANNKE CZ400 Specifications
(Model Number: I91BK)

Camera	Image Sensor	1/3" OmniVision Progressive Scan CMOS
	Video Resolution	24 fps (2560 X 1440), 30 fps (2048 X 1536, 1920 X 1080, 1280 X 960, 1280 X 720)
	Video Compression	H.265+/H.265/H.264+/H.264
	Video Bitrate	32 Kbps - 16,384 Kbps
	Lens	2.8-12 mm, 4X Optical Zoom, 16X Digital Zoom
	Min. Illumination	Color: 0.005 Lux @ (f/1.6, AGC On), B/W: 0.001 Lux @ (f/1.6, AGC On), 0 Lux with IR
	Angle of View	Horizontal Field of View: 33° - 100° (Wide-Tele) Vertical Field of View: 18° - 53° (Wide-Tele) Diagonal Field of View: 37.5° - 119° (Wide-Tele)
	PT Movement Range	Pan: 0° - 330°, Tilt: 0° - 90°
	PT Speed	Configurable, 0.1°/s - 100°/s, Preset Speed: 100°/s
	Number of Infrared LEDs	4 pcs
	Night Vision Distance	Up to 65 ft/20 m
	Image Enhancement	3D DNR, HLC, EIS, Regional Exposure, Regional focus
	Wide Dynamic Range	120 dB True WDR
	Protocols	Support ONVIF and Other Protocols
	Smart Event	Intrusion Detection, Line Crossing Detection, Region Entrance Detection, Region Exiting Detection, Object Removal Detection, Unattended Baggage Detection, Audio Exception Detection
	Face Detection	Yes
	IR-Cut Filter	Yes
Audio	Built-in Mic; Support 1-CH Audio Input and 1-CH Audio Output	
Ethernet	RJ45 X1 (10 M/100 M)	
General	Material	Aluminum Alloy, PC, PC + ABS
	Color	White
	Operating Power	DC 12 V; PoE (802.3at)
	Storage	Support MicroSD Card (up to 256 GB) Local Storage and NAS
	Operating Temperature	-4° to 140° F (-20° to 60° C)
	Indoor/Outdoor	Indoor/Outdoor
	Protection Level	IP66, IK10, TVS 4,000 V Lightning Protection, Surge Protection, and Voltage Transient Protection
	Dimension	P5.15" X 4.00" (P130.7 mm X 101.7 mm)
Weight	Approximately 1.17 lbs. (0.53 kg)	