

H500 SMP PoE System Specifications		
C500 Bullet PoE Security Camera Specifications (Model Number: IS1DE)		
Camera	Image Sensor	1/3" Progressive Scan CMOS
	Video Resolution	5MP (2560 X 1920 @15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265+/H.265/H.264+/H.264
	Video Bitrate	32 Kbps — 8 Mbps
	Lens	2.8 mm
	Min. Illumination	Color: 0.01 Lux @(F2.0, AGC On)
	Angle of View	Horizontal FoV 71.5°, Vertical FoV 53°, Diagonal FoV 91°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
General	Ethernet	RJ45 X1 (10 M/100 M)
	Housing	Metal & Plastic
	Color	White
	Operating Power	DC 12 V; PoE (802.3af)
	Operating Temperature	-22 °F — 140 °F/-30 °C — 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L X W X H)	6.8" X 2.6" X 2.72"/172.7 X 66 X 69.1 mm
	Weight	0.7 lb./300 g
C500 Turret PoE Security Camera Specifications (Model Number: IS1DF)		
Camera	Image Sensor	1/3" Progressive Scan CMOS
	Video Resolution	5MP (2560 X 1920 @15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265+/H.265/H.264+/H.264
	Video Bitrate	32 Kbps — 8 Mbps
	Lens	2.8 mm
	Min. Illumination	Color: 0.01 Lux @(F1.2, AGC On)
	Angle of View	Horizontal FoV 71.5°, Vertical FoV 53°, Diagonal FoV 91°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
General	Ethernet	RJ45 X1 (10 M/100 M)
	Housing	Metal & Plastic
	Color	White
	Operating Power	DC 12 V; PoE (802.3af)
	Operating Temperature	-22 °F — 140 °F/-30 °C — 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L X W X H)	4.3" X 3.7"/110 X 93.2 mm
	Weight	0.9 lb./400 g
C500 Dome PoE Security Camera Specifications (Model Number: IS1DK)		
Camera	Image Sensor	1/2.7" Progressive Scan CMOS
	Video Resolution	5MP (2560 X 1920 @15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265/H.264
	Video Bitrate	32 Kbps — 8 Mbps
	Lens	4 mm
	Min. Illumination	Color: 0.01 Lux @(F1.2, AGC On)
	Angle of View	75°
	Number of Infrared LEDs	30 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
General	Ethernet	RJ45 X1 (10 M/100 M)
	Housing	Metal & Plastic
	Color	White
	Operating Power	DC12V/PoE (802.3af)
	Operating Temperature	-22 °F — 140 °F / -30 °C — 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Vandal-Proof Rating	IK10
	Dimension (L X W X H)	4.4" X 3.2"/111 X 82.4 mm
	Weight	0.9 lb./400 g
ANNKE 8-Channel 6MP PoE NVR (Model Number: N48PBB)		
Video & Audio	Video Compression	H.265+/H.265/ H.264+/H.264
	IP Video Input	8CH PoE
	Video Output	HDMI & VGA up to 1080p
	Incoming Bandwidth	60 M
	Max Recording Resolution	Up to 6MP
	Max Playback Resolution	Up to 6MP
	Max Playback Channel	8CH
	Max Playback Capacity	4CH @1080p; 1CH @6MP
	ONVIF Protocols	Support
	Hard Drive	HDD
HDD Capacity		Up to 6 TB Capacity
External Interface	Network Interface	RJ45 X1 (10/100 M)
	PoE	8 Ports (IEEE802.3at/af)
	USB	2X USB 2.0
General	Operating Power	DC 48 V
	Power Consumption	≤10 W (Without HDD and PoE) PoE: Max 25.5 W for Single Port
	Working Temperature	14 °F — 131 °F/-10 °C — +55 °C
	Dimensions (W X H X D)	10.4" X 8.9" X 1.9"/265 X 225 X 48 mm
	Weight (Without Hard Disk)	2.2 lbs./1 kg