

| <b>ANNKE H800 16-Channel 4K PoE System Specifications</b>                      |  |   |
|--|--|---|
| <b>C800 Bullet PoE Security Camera Specifications</b><br>(Model Number: 1918D) |  |   |
| Camera   | Image Sensor   | 1/2.5" Sony Progressive Scan CMOS   |
|  | Video Resolution   | BMP (3840 X 2160@15 fps)  |
|  | Signal System  | PAL/NTSC  |
|  | Video Compression  | H.265/H.264   |
|  | Video Bitrate  | 32 Kbps - 16 Mbps   |
|  | Lens   | 2.8 mm  |
|  | Min. Illumination  | 0.01 Lux @(F1.2, AGC On)  |
|  | Angle of View  | 102°  |
|  | Number of Infrared LEDs  | 2 pcs   |
|  | Night Vision Distance  | Up to 100 ft/30 m   |
|  | DNR  | 3D DNR  |
|  | Wide Dynamic Range   | Digital WDR   |
|  | DNMF   | Support   |
|  | IR-Cut Filter  | Yes   |
| Ethernet   | RJ45 X1 (10 M/100 M)   |   |
| Housing  | Metal  |   |
| Color  | White  |   |
| General  | Operating Power  | PoE (802.3af)   |
|  | Operating Temperature  | -22 °F - 140 °F/30 °C - 60 °C   |
|  | Indoor/Outdoor   | Indoor/Outdoor  |
|  | Weatherproof Rating  | IP67  |
|  | Dimension  | 6.3" X 3.8"/155 X 70 mm   |
|  | Weight   | 0.9 lbs./410 g  |
|  | <b>C800 Turret PoE Security Camera Specifications</b><br>(Model Number: 1918F) |   |
|  | Camera   | Image Sensor  |
| Video Resolution   |  | BMP (3840 X 2160)   |
| Signal System  |  | PAL/NTSC  |
| Video Compression  |  | H.265/H.265+/H.264+/H.264   |
| Video Bitrate  |  | 32 Kbps - 16 Mbps   |
| Lens   |  | 2.8 mm  |
| Min. Illumination  |  | 0.01 Lux @(F1.2, AGC On)  |
| Angle of View  |  | Diagonal FoV: 124°  |
| Number of Infrared LEDs  |  | 1 pc  |
| Night Vision Distance  |  | Up to 100 ft/30 m   |
| DNR  |  | 3D DNR  |
| Wide Dynamic Range   |  | 120 dB True WDR   |
| DNMF   |  | Support   |
| IR-Cut Filter  |  | Yes   |
| Ethernet   | RJ45 X1 (10 M/100 M)   |   |
| Housing  | Metal & Plastic  |   |
| Color  | White  |   |
| General  | Operating Power  | DC 12 V; PoE (802.3af)  |
|  | Storage  | Built-in MicroSD/SDHC/SDXC Slot, up to 128 GB   |
|  | Operating Temperature  | -22 °F - 140 °F/30 °C - 60 °C   |
|  | Indoor/Outdoor   | Indoor/Outdoor  |
|  | Weatherproof Rating  | IP67  |
|  | Dimension  | 5" X 3.8"/127.3 X 95.9 mm   |
|  | Weight   | 1.4 lbs./620 g  |
|  | <b>C800 Dome PoE Security Camera Specifications</b><br>(Model Number: 1918E)   |   |
| Camera   | Image Sensor   | 1/2.5" Sony Progressive Scan CMOS   |
|  | Video Resolution   | BMP (3840 X 2160@15 fps)  |
|  | Signal System  | PAL/NTSC  |
|  | Video Compression  | H.265/H.264   |
|  | Video Bitrate  | 32 Kbps - 16 Mbps   |
|  | Lens   | 4 mm  |
|  | Min. Illumination  | 0.01 Lux @(F1.2, AGC On)  |
|  | Angle of View  | 79°   |
|  | Number of Infrared LEDs  | 3 pcs   |
|  | Night Vision Distance  | Up to 100 ft/30 m   |
|  | DNR  | 3D DNR  |
|  | Wide Dynamic Range   | Digital WDR   |
|  | DNMF   | Support   |
|  | IR-Cut Filter  | Yes   |
| Ethernet   | RJ45 X1 (10 M/100 M)   |   |
| Housing  | Metal & Plastic  |   |
| Color  | White  |   |
| General  | Operating Power  | DC 12 V; PoE (802.3af)  |
|  | Operating Temperature  | -22 °F - 140 °F/30 °C - 60 °C   |
|  | Indoor/Outdoor   | Indoor/Outdoor  |
|  | Weatherproof Rating  | IP67  |
|  | Vandal Proof Rating  | IK10  |
|  | Dimension  | 4.4" X 3.2"/111 X 82.4 mm   |
|  | Weight   | 1.1 lbs./500 g  |
|  | <b>C800 Zoom PoE Security Camera Specifications</b><br>(Model Number: 1918G)   |   |
| Camera   | Image Sensor   | 1/2.5" Sony STARVIS IMX274 Image Sensor   |
|  | Video Resolution   | BMP (3840 X 2160@12.5/15 fps)   |
|  | Signal System  | PAL/NTSC  |
|  | Video Compression  | H.265+/H.265/H.264+/H.264   |
|  | Video Bit Rate   | 32 Kbps - 16 Mbps   |
|  | Lens   | 2.8-12 mm, 4X Optical Zoom  |
|  | Min. Illumination  | Color: 0.018 Lux @(F1.6, AGC On)  |
|  | Angle of View  | Horizontal Field of View: 34.5° - 105°<br>Vertical Field of View: 19° - 55°<br>Diagonal Field of View: 40° - 125° |
|  | Number of Infrared LEDs  | 4 pcs   |
|  | Night Vision Distance  | Up to 164 ft/50 m   |
|  | DNR  | 3D DNR  |
|  | Wide Dynamic Range   | 120 dB True WDR   |
|  | DNMF   | Support   |
|  | Behavior Analysis  | Line Crossing Detection & Intrusion Detection   |
| Face Detection   | Yes  |   |
| IR-Cut Filter  | Yes  |   |
| Ethernet   | RJ45 X1 (10 M/100 M)   |   |
| Housing  | Metal  |   |
| Color  | White  |   |
| General  | Operating Power  | DC 12 V; PoE (802.3af)  |
|  | Storage  | Support MicroSD Card (up to 328 GB) Local Storage and NMS   |
|  | Operating Temperature  | -22 °F - 140 °F/30 °C - 60 °C   |
|  | Indoor/Outdoor   | Indoor/Outdoor  |
|  | Weatherproof Rating  | IP67  |
|  | Dimension  | 4.4" X 1.7"/105 X 297.5 mm  |
|  | Weight   | 2.9 lbs./1,333 g  |
|  | <b>ANNKE 16 Channel PoE NVR</b><br>(Model Number: N46PCK)                      |   |
| Video & Audio  | Video Compression  | H.264+/H.264/H.265+/H.265+/MPEG4  |
|  | IP Video Input   | 16CH PoE  |
|  | Video Output   | HDMI up to 4K; VGA up to 1080p  |
|  | Audio Input/Output   | 1/1 RCA   |
|  | Incoming Bandwidth   | 160 M   |
|  | Max Recording Resolution   | Up to BMP (3840 X 2160)   |
|  | Max Playback Resolution  | Up to BMP (3840 X 2160)   |
|  | Max Playback Channel   | 16CH  |
| Hard Drive   | Max Playback Capacity  | 4CH @ 1080p, 1CH @ 8MP  |
|  | DNMF Protocol  | Support   |
| External Interface   | HDD  | 2 SATA Interface  |
|  | HDD Capacity   | Up to 6 TB Capacity   |
| General  | Network Interface  | RJ45 X1 (10/100/1000 M)   |
|  | POE  | 16 Ports (IEEE802.3af/at)   |
|  | IOS  | X1 USB 2.0  |
|  | Operating Power  | AC 100-240 V  |
| General  | Power Consumption  | ≤15 W (Without HDD and PoE)   |
|  | Working Temperature  | PoE: Max 21.5 W for Single Port<br>14 °F - 113 °F/5 °C - 45 °C  |
|  | Dimensions (W X H X D)   | 15.2" X 12.4" X 2.0"/385 X 315 X 52 mm  |
|  | Weight (Without Hard Disk)   | 6.6 lbs./3 kg   |