

ANNKE HD08 8-Channel 4K PoE System Specifications		
CB00 Bullet PoE Security Camera Specifications (Model Number: 1918D)		
Camera	Image Sensor	1/2.5" Sony Progressive Scan CMOS
	Video Resolution	BMP (3840 X 2160@15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265/H.264
	Video Bitrate	32 Kbps - 16 Mbps
	Lens	2.8 mm
	Min. Illumination	0.01 Lux @(F1.2, AGC On)
	Angle of View	102°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	DNMF	Support
	IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)	
Housing	Metal	
Color	White	
General	Operating Power	PoE (802.3af)
	Operating Temperature	-22 °F - 140 °F/30 °C - 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension	6.3" x 3.8"/155 X 70 mm
	Weight	0.9 lbs./410 g
	CB00 Turret PoE Security Camera Specifications (Model Number: 1918F)	
	Camera	Image Sensor
Video Resolution		BMP (3840 X 2160)
Signal System		PAL/NTSC
Video Compression		H.265/H.265+/H.264+/H.264
Video Bitrate		32 Kbps - 16 Mbps
Lens		2.8 mm
Min. Illumination		0.01 Lux @(F1.2, AGC On)
Angle of View		Diagonal FoV: 124°
Number of Infrared LEDs		1 pc
Night Vision Distance		Up to 100 ft/30 m
DNR		3D DNR
Wide Dynamic Range		120 dB True WDR
DNMF		Support
IR-Cut Filter		Yes
Ethernet	RJ45 X1 (10 M/100 M)	
Housing	Metal & Plastic	
Color	White	
General	Operating Power	DC 12 V; PoE (802.3af)
	Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 128 GB
	Operating Temperature	-22 °F - 140 °F/30 °C - 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension	5" x 3.8"/127.3 X 95.9 mm
	Weight	1.4 lbs./620 g
	CB00 Dome PoE Security Camera Specifications (Model Number: 1918E)	
Camera	Image Sensor	1/2.5" Sony Progressive Scan CMOS
	Video Resolution	BMP (3840 X 2160@15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265/H.264
	Video Bitrate	32 Kbps - 16 Mbps
	Lens	4 mm
	Min. Illumination	0.01 Lux @(F1.2, AGC On)
	Angle of View	79°
	Number of Infrared LEDs	3 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	DNMF	Support
	IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)	
Housing	Metal & Plastic	
Color	White	
General	Operating Power	DC 12 V; PoE (802.3af)
	Operating Temperature	-22 °F - 140 °F/30 °C - 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Vandal Proof Rating	IK10
	Dimension	4.4" x 3.2"/111 X 82.4 mm
	Weight	1.1 lbs./500 g
	CB00 Zoom PoE Security Camera Specifications (Model Number: 1918G)	
Camera	Image Sensor	1/2.5" Sony STARVIS IMX274 Image Sensor
	Video Resolution	BMP (3840 X 2160@12.5/15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265+/H.265/H.264+/H.264
	Video Bit Rate	32 Kbps - 16 Mbps
	Lens	2.8-12 mm, 4X Optical Zoom
	Min. Illumination	Color: 0.018 Lux @(F1.6, AGC On)
	Angle of View	Horizontal Field of View: 34.5° - 105° Vertical Field of View: 19° - 55° Diagonal Field of View: 40° - 125°
	Number of Infrared LEDs	4 pcs
	Night Vision Distance	Up to 164 ft/50 m
	DNR	3D DNR
	Wide Dynamic Range	120 dB True WDR
	DNMF	Support
	Behavior Analysis	Line Crossing Detection & Intrusion Detection
Face Detection	Yes	
IR-Cut Filter	Yes	
Ethernet	RJ45 X1 (10 M/100 M)	
Housing	Metal	
Color	White	
General	Operating Power	DC 12 V; PoE (802.3af)
	Storage	Support MicroSD Card (up to 328 GB) Local Storage and NMS
	Operating Temperature	-22 °F - 140 °F/30 °C - 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension	4.4" x 1.7"/105 X 29.5 mm
	Weight	2.9 lbs./1,333 g
	ANNKE 8 Channel PoE NVR (Model Number: N8PAW)	
Video & Audio	Video Compression	H.264+/H.264/H.265+/H.265+/MPEG4
	IP Video Input	8CH Input
	Video Output	HDMI up to 4K; VGA up to 1080p
	Audio Input/Output	1/1 RCA
	Incoming Bandwidth	80 M
	Max Recording Resolution	Up to BMP (3840 X 2160)
	Max Playback Resolution	Up to BMP (3840 X 2160)
	Max Playback Channel	8CH
Max Playback Capacity	4CH @ 1080p; 1CH @ 8MP	
DNMF Protocol	Support	
Hard Drive	HDD	1 SATA Interface
	HDD Capacity	Up to 6 TB Capacity for Each HDD
External Interface	Network Interface	RJ45 X1 (10/100/1000 M)
	POE	8 Ports (IEEE802.3afVaf)
	USB	X1 USB 2.0
General	Operating Power	DC 48 V
	Power Consumption	≤10 W (Without HDD and PoE)
	Working Temperature	PoE: Max 23.5 W for Single Port 14 °F - 113 °F/10 °C - 45 °C
	Dimensions (W X H X D)	12.4" x 9.4" x 1.9"/315 X 240 X 48 mm
	Weight (Without Hard Disk)	2.2 lbs./1 kg