
		Key features	
		<ul style="list-style-type: none"> ★ 8MP IR Network Bullet Camera ★ Efficient H.265+ compression technology ★ 4mm lens with diagonal FOV 98° brings everything back to life ★ Up to 100ft night vision with Smart IR ★ Built-in microphone for real-time audio security ★ Support up to 256GB SD card storage ★ Clear imaging even with strong back lighting due to 120 dB WDR ★ EXIR 2.0: advanced infrared technology with long IR range up to 30m ★ IP67 Dust and Waterproof Rating ★ Support PoE (Power over Ethernet)&DC12V 	
Model Number		I91BL*4	
IP Camera			
Camera	Image sensor	1/2.5" Progressive Scan CMOS	
	Video Resolution	50Hz: 12.5 fps (3840×2160, 2560×1440, 1920×1080, 1280×720) 60Hz: 15 fps(3840×2160, 2560×1440, 1920×1080, 1280×720)	
	Sub Stream	50Hz: 25 fps (640×480, 640 360) 60Hz: 30 fps (640×480, 640 360)	
	Video compression	H.265+/H.265	
	Video Bit Rate	32Kbps~16Mbps	
	Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC	
	Audio input/output	Bulit-in Microphone	
	Lens	4mm	
	Min. Illumination	0.01 Lux @(F2.0, AGC ON)	
	Angle of View	Horizontal FOV 83°, vertical FOV 44°, diagonal FOV 98°	
	Number of Infra-Red LEDs	2 pcs	
	Night Vision Distance	Up to 100ft/30m	
	DNR	3D DNR	
	Wide Dynamic Range	120dB WDR	
	Network Storage	Local storage & NAS (NFS, SMB/CIFS)	
	Onvif	Support	
	Day/Night Switch	Day, Night, Auto, Schedule	
Ethernet	RJ45 x 1(10M/100M)		
General	Housing	Aluminum alloy for main body	
	Color	White	
	Operating Power	PoE (802.3af), 12 VDC ± 25%	
	Storage	Built-in micro SD/SDHC/SDXC slot, up to 256 GB	
	Hardware Reset	Yes	
	Operating Temperature	-22 °F – 140 °F /-30 °C – 60 °C	
	Indoor/Outdoor	Indoor/Outdoor	
	Weatherproof Rating	IP67	
	Dimension (L x W x H)	171.4 × 69.7 × 67.9 mm (6.7" × 2.7" × 2.7")	
Weight	0.9lbs /430g		
Packaging Contents			
Camera	4		
Ethernet Cable	60ft/18m x2;100ft/30m x2		
Power Adapter	-		
Mounting Screws Bag	4		
User's Manual For Camera	1		

		Key features	
		<ul style="list-style-type: none"> ★ 8MP IR Network Dome Camera ★ Efficient H.265+ compression technology ★ 4mm lens with diagonal FOV 98° brings everything back to life ★ Up to 100ft night vision with Smart IR ★ Built-in microphone for real-time audio security ★ Support up to 256GB SD card storage ★ Clear imaging even with strong back lighting due to 120 dB WDR ★ EXIR 2.0: advanced infrared technology with long IR range up to 30m ★ IP67 Dust and Waterproof Rating&IK10 ★ Support PoE (Power over Ethernet)&DC12V 	
Model Number		I91BN*4	
IP Camera			
Camera	Image Sensor	1/2.5" Progressive Scan CMOS	
	Video Resolution	50 Hz: 12.5 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720) 60 Hz: 15 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720)	
	Sub Stream	50Hz: 25 fps (640 X 480, 640 X 360) 60Hz: 30 fps (640 X 480, 640 X 360)	
	Video Compression	H.265+/H.265	
	Video Bitrate	32 Kbps — 16 Mbps	
	Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC	
	Audio Input/Output	Built-in Microphone	
	Lens	4 mm	
	Min. Illumination	0.01 Lux@(F2.0, AGC On)	
	Angle of View	Horizontal FOV 83°, vertical FOV 44°, diagonal FOV 98°	
	Number of Infrared LEDs	2 pcs	
	Night Vision Distance	Up to 100 ft/30 m	
	DNR	3D DNR	
	Wide Dynamic Range	120 dB WDR	
	Network Storage	Local Storage & NAS (NFS, SMB/CIFS)	
	ONVIF	Support	
	Day/Night Switch	Day, Night, Auto, Schedule	
Ethernet	RJ45 X1 (10 M/100 M)		
General	Housing	Aluminum Alloy for Main Body	
	Color	White	
	Operating Power	PoE (802.3af), 12 V DC ± 25%	
	Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 256 GB	
	Hardware Reset	Yes	
	Operating Temperature	-22 °F – 140 °F /-30 °C – 60 °C	
	Indoor/Outdoor	Indoor/Outdoor	
	Weatherproof Rating	IP67 & IK10	
	Dimension (L X W X H)	Ø120 X 92.2 mm (4.7" X 3.6")	
	Weight	0.9 lb./420 g	
	Packaging Contents		
	Camera	4	
	Ethernet Cable	60ft/18m x2;100ft/30m x2	
	Power Adapter	-	
	Mounting Screws Bag	4	
	User's Manual For Camera	1	



Key features

- ★ 8MP IR Network Turret Camera
- ★ Motion detection 2.0 with human & Vehicle Detection
- ★ Efficient H.265+ compression technology
- ★ 4mm lens with diagonal FOV 98° brings everything back to life
- ★ Up to 100ft night vision with Smart IR
- ★ Built-in microphone for real-time audio security
- ★ Support up to 256GB SD card storage
- ★ Clear imaging even with strong back lighting due to 120 dB WDR
- ★ EXIR 2.0: advanced infrared technology with long IR range up to 30m
- ★ IP67 Dust and Waterproof Rating
- ★ Support PoE (Power over Ethernet)&DC12V

Model Number

I91BS*4

IP Camera

Camera	Image Sensor	1/2.5" Progressive Scan CMOS
	Video Resolution	50 Hz: 12.5 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720) 60 Hz: 15 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720)
	Sub Stream	50 Hz: 25 fps (640 X 480, 640 X 360) 60 Hz: 30 fps (640 X 480, 640 X 360)
	Video Compression	H.265+/H.265
	Video Bitrate	32 Kbps ~ 16 Mbps
	Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC
	Audio Input/Output	Built-in Microphone
	Lens	4 mm
	Min. Illumination	0.01 Lux@(F2.0, AGC On)
	Angle of View	Horizontal FOV 83°, vertical FOV 44°, diagonal FOV 98°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	120 dB WDR
	Network Storage	Local Storage & NAS (NFS, SMB/CIFS)
	API	Open Network Video Interface Version 18.12
	Motion detection 2.0	Support, include Human & Vehicle detection
Day/Night Switch	Day, Night, Auto, Schedule	
Ethernet	RJ45 X1 (10 M/100 M)	
General	Housing	Plastic & Metal
	Color	White
	Operating Power	PoE (802.3af), 12 V DC ± 25%
	Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 256 GB
	Hardware Reset	Yes
	Operating Temperature	-22 °F - 140 °F/-30 °C - 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
Dimension (L X W X H)	Ø109.9 mm × 103.6 mm (Ø4.33" × 4.08")	
Weight	0.9 lb./390 g	

Packaging Contents

Camera	4
Ethernet Cable	60ft/18m x2;100ft/30m x2
Mounting Screws Bag	4
Surveillance Sign	4
User's Manual For Camera	1