

ANNKE S300 Specifications

PIR Bullet Camera Specifications

(Model Number: CT1DL)

Camera	Image Sensor	2MP CMOS Image Sensor
	Video Resolution	1920 (H) X 1080 (V)
	Signal System	PAL/NTSC
	Frame Rate	PAL: 1080p@25 fps; NTSC: 1080p@30 fps
	Lens	3.6 mm
	Min. Illumination	Color: 0.01 Lux @(F1.2, AGC On), 0 Lux with IR
	Angle of View	82.2°
	Number of Infrared LEDs	1
	PIR Detection	Support
	White Light	Alarm/Off
	OSD Menu	Yes
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	IR-Cut Filter	Yes
Video Output	HD BNC X1	
General	Housing	Plastic
	Color	White
	Operating Power	DC 12 V
	Operating Temperature	-40 °F – 140 °F/-40 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L X W X H)	7.08" X 2.76" X 2.68"/179.8 X 70 X 68 mm
	Weight	0.43 lb./195 g

PIR Dome Camera Specifications

(Model Number: CT1DM)

Camera	Image Sensor	2MP CMOS Image Sensor
	Video Resolution	1920 (H) X 1080 (V)
	Signal System	PAL/NTSC
	Frame Rate	PAL: 1080p@25 fps; NTSC: 1080p@30 fps
	Lens	3.6 mm
	Min. Illumination	Color: 0.01 Lux @(F1.2,AGC On), 0 Lux with IR
	Angle of View	82.2°
	Number of Infrared LEDs	1
	PIR Detection	Support
	Visual Alarm	White Light

	OSD Menu	Yes
	Night Vision Distance	Up to 66 ft/20 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	IR-Cut Filter	Yes
	Video Output	HD BNC X1
General	Material	Plastic
	Color	White
	Operating Power	DC 12 V
	Operating Temperature	-40 °F – 140 °F/-40 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L X W X H)	Φ4.32" X 3.53"/Φ109.8 X 89.75 mm
	Weight	0.53 lb./242 g

DVR Specifications
(Model Number: DW41JD/DW81KD/DW61LD)

Video & Audio	Video Compression	H.264+/H.264/H.265/H.265+
	Video Input	8CH Analog HD/Analog + 2CH IP Cameras 16CH Analog HD/Analog + 2CH IP Cameras
	Video Output	4/8CH: HDMI and VGA up to 1080p 16CH: HDMI up to 4K (3840 X 2160) and VGA up to 2K (2560 X 1440)
	Audio Input/Output	1/1 RCA
	Analog HD Recording Resolution	5MP Lite/3MP/1080p/720p/VGA/WD1/4CIF/CIF@12 fps
	Analog HD Playback Resolution	5MP Lite/3MP/1080p/720p/VGA/WD1/4CIF/CIF
	IPC Recording Resolution	Up to 6MP
	IPC Playback Resolution	Up to 6MP
	Max Playback Channel	4CH: 4-CH 8CH: 8-CH 16CH: 16-CH
	ONVIF Protocols	Support
Hard Drive	HDD	1 SATA Interface
	HDD Capacity	Up to 6 TB Capacity
General	Network Interface	RJ45 X1 (10/100 M)
	USB	USB 2.0 X2
	Operating Power	DC 12 V
	Working Temperature	-14 °F – 131 °F/-10 °C – 55 °C
	Dimensions (W X H X D)	260 X 222 X 45 mm
	Weight (Without Hard Disk)	4CH: ≤ 1 kg (2.2 lbs.) (Without HDD) 8CH: ≤ 1 kg (2.2 lbs.) (Without HDD) 16CH: ≤ 1.2 kg (2.6 lbs.) (Without HDD)