

ANNKE C800 Bullet PoE Security Camera Specifications (Model Number: I91BD)		
Camera	Image Sensor	1/2.5" Sony Progressive Scan CMOS
	Video Resolution	8MP (3840 X 2160@15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265/H.264
	Video Bitrate	32 Kbps - 16 Mbps
	Lens	2.8 mm
	Min. Illumination	0.01 Lux @(F1.2, AGC On)
	Angle of View	102°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)	
General	Housing	Metal
	Color	White
	Operating Power	PoE (802.3af)
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension	6.1" X 2.8"/155 X 70 mm
	Weight	0.9 lb./410 g
ANNKE C800 Turret Specifications (Model Number: I91BM)		
Camera	Image Sensor	1/2.5" Progressive Scan CMOS
	Video Resolution	50 Hz: 12.5 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720) 60 Hz: 15 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720)
	Sub Stream	50 Hz: 25 fps (640 X 480, 640 X 360) 60 Hz: 30 fps (640 X 480, 640 X 360)
	Video Compression	H.265+/H.265
	Video Bitrate	32 Kbps ~ 16 Mbps
	Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC
	Audio Input/Output	Built-in Microphone
	Lens	2.8 mm
	Min. Illumination	0.01 Lux@(F2.0, AGC On)
	Angle of View	Horizontal FoV 102°, Vertical FoV 53°, Diagonal FoV 123°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	120 dB WDR
	Network Storage	Local Storage & NAS (NFS, SMB/CIFS)
	ONVIF	Support
	Day/Night Switch	Day, Night, Auto, Schedule
Ethernet	RJ45 X1 (10 M/100 M)	
General	Housing	Plastic & Metal
	Color	White
	Operating Power	PoE (802.3af), 12 V DC ± 25%
	Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 256 GB
	Hardware Reset	Yes
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
Dimension (L X W X H)	∅110 X 81.25 mm (∅4.33" X 3.20")	
Weight	0.9 lb./390 g	
ANNKE C800 Dome PoE Security Camera Specifications (Model Number: I91BE)		
Camera	Image Sensor	1/2.5" Sony Progressive Scan CMOS
	Video Resolution	8MP (3840 X 2160@15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265/H.264
	Video Bitrate	32 Kbps - 16 Mbps
	Lens	4 mm
	Min. Illumination	0.01 Lux @ (F1.2, AGC On)
	Angle of View	79°
	Number of Infrared LEDs	3 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)	
General	Housing	Metal & Plastic
	Color	White
	Operating Power	DC 12 V; PoE (802.3af)
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Vandal-Proof Rating	IK10
	Dimension	4.4" X 3.2"/111 X 82.4 mm
Weight	1.1 lbs./500 g	