

ANNKE C500 Bullet PoE Security Camera Specifications (Model Number: I51DE)		
Camera	Image Sensor	1/3" OmniVision Progressive Scan CMOS
	Video Resolution	5MP (2560 X 1920@15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265+/H.265/H.264+/H.264
	Video Bitrate	32 Kbps - 8 Mbps
	Lens	2.8 mm
	Min. Illumination	Color: 0.01 Lux @(F2.0, AGC On)
	Angle of View	Horizontal FoV 71.5°, Vertical FoV 53°, Diagonal FoV 91°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)	
General	Housing	Metal & Plastic
	Color	White
	Operating Power	DC 12 V; PoE (802.3af)
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L X W X H)	6.8" X 2.6" X 2.72"/172.7 X 66 X 69.1 mm
Weight	0.7 lb./300 g	
ANNKE C500 Turret PoE Security Camera Specifications (Model Number: I51DF)		
Camera	Image Sensor	1/3" OmniVision Progressive Scan CMOS
	Video Resolution	5MP (2560 X 1920@15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265+/H.265/H.264+/H.264
	Video Bitrate	32 Kbps - 8 Mbps
	Lens	2.8 mm
	Min. Illumination	Color: 0.01 Lux @(F1.2, AGC On)
	Angle of View	Horizontal FoV 71.5°, Vertical FoV 53°, Diagonal FoV 91°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)	
General	Housing	Metal & Plastic
	Color	White
	Operating Power	DC 12 V; PoE (802.3af)
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension	4.3" X 3.7"/110 X 93.2 mm
Weight	0.9 lb./400 g	
ANNKE C500 Dome PoE Security Camera Specifications (Model Number: I51DK)		
Camera	Image Sensor	1/2.7" OmniVision Progressive Scan CMOS
	Video Resolution	5MP (2560 X 1920@15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265/H.264
	Video Bitrate	32 Kbps - 8 Mbps
	Lens	4 mm
	Min. Illumination	Color: 0.01 Lux @(F1.2, AGC On)
	Angle of View	75°
	Number of Infrared LEDs	30 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)	
General	Housing	Metal & Plastic
	Color	White
	Operating Power	DC 12 V; PoE (802.3af)
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Vandal-Proof Rating	IK10
Dimension	4.4" X 3.2"/111 X 82.4 mm	
Weight	0.9 lb./400 g	