

# Suspension LIFT KITS

9K817



## Honda Rancher lift kits installation instructions

Please note that it is recommended that all kits be installed by a professional shop.

### FRONT

1. Raise front off ground; secure with jack stands.
2. Remove Wheels.
3. Disconnect the top of the shocks from the frame shock mount.
4. Remove the bolt of the front carrier, just over the shock. Keep the OEM bolt.
5. Install the Front Brackets to Shock Mount with hardware as the picture shown.



6. Install Shocks to the Front Brackets with stock hardware.



7. Repeat the same steps for the opposite side.

8. Tighten all hardware completely (make sure all the hardware tighten). Reinstall Wheels.

### REAR

1. Raise rear off ground; secure with jack stands.

2. Remove Wheels.

3. Disconnect the bottom of the shock from the swing arm.

4. Unbolt the bolt of the gearbox that is face off the slotted hole on the Rear Bracket. Re-use this bolt to secure the bracket to the swing arm.



5. Install the Rear Bracket with hardware as the picture shown.

6. Install Shocks to Rear Brackets with stock hardware. **When you install the gaskets, check the shocks back to original installation position.**



7. Tighten all hardware completely. Reinstall Wheels.

**Re-torque all bolts and nuts on the lift kits after 100-200 miles of driving.**

## Thank you for the purchases!

It is our honor to help you. So please write us about what you think and what you need.

We will reply you ASAP and try our overwhelming best to help you solve the problem.

Please feel free to contact us via eBay message or Amazon tools.

E-mail: [speed@nbgoldenlion.com](mailto:speed@nbgoldenlion.com)

Amazon:

1. Visit [www.amazon.com/your-orders](http://www.amazon.com/your-orders)

2. Find your product

3. Click on "contact seller"

4. Include your order #

eBay:

1. Visit [www.ebay.com](http://www.ebay.com)

2. Click on "My eBay"

3. Find your product

4. Click on "More actions"

5. Click on "Contact seller"