

FIERYRED®
4x4 EQUIPMENT

4X4 RECOVERY KIT
Soft Shackle & Winch Ring
INSTRUCTION MANUAL



Please read this manual carefully before use

K-WIN-RING100-S

V1.0

Fieryred, founded in March, 2016 and born of the passion to fulfill four-wheel drive lovers' demand for affordable, yet high quality 4x4 equipment, takes prides in designing, engineering and providing rock solid 4x4 products to let you rediscover the fun of off-roading.

Based in the United States, Fieryred is a professional supplier of 4x4 equipment, currently provides off-road recovery gears & tools as well as aftermarket vehicle parts that are designed to offer you ultimate experience with exceptional value.

It is the passion, coupled with a continuing commitment to quality and unswerving dedication to customer, that distinguishes Fieryred from the competition. At Fieryred, we strive to excel your expectation, and permeate that conviction into every product that wears the Fieryred brand.

Wherever your passion takes you, Make Your Own Path.

WARNINGS AND SAFETY INSTRUCTIONS

- Only attach the soft shackle to recovery points which are designed for compatibility with soft shackles. This typically means they have rounded edges around the eye to prevent damaging the fibres of the soft shackle.
- The soft shackle is ideal for connecting snatch straps, kinetic ropes and winch ropes to recovery points, or for joining straps or ropes together.
- Please note that the soft shackle is designed for recovery use only; it cannot be used in place of D-shackles for towing and other constant load applications.
- The snatch ring is designed to fit soft shackles and synthetic winch ropes only.
- Check the soft shackle for signs of wear or damage before use; if fibres are cut, worn or fraying, do not use the soft shackle.
- Inspect the snatch ring before use; if there is any damage, cracks or deformation, do not use the snatch ring.
- Never modify the soft shackle or the snatch ring.
- Always wear safety gear when performing recovery, including gloves and glasses.

CARE AND MAINTENANCE

- To maximise durability and performance, the soft shackle and the snatch ring should be kept clean and dry and stored in the protective storage bag supplied.
- The soft shackle should be stored away from direct sunlight (UV) exposure when not in use.
- Do not expose the soft shackle to petrochemical products or excessive heat as this may melt / damage or weaken the fibres.
- The synthetic rope is impervious to water, but sand, dirt and grit can cause wear and abrasion to the rope fibres.
- If the soft shackle gets dirty, it can be washed in clean water, then left to air dry away from direct sunlight before packing away when completely dry.

CONTENTS

Soft Shackle x1
Winch Ring x1
Storage Bag x1

SPECIFICATIONS

Shackle
Shackle Color: Vermilion
Shackle Material:UHMWPE
Shackle Rope Length (Without Knot & Eye): 20.08" (51cm)
Shackle Rope Diameter: 0.98" (25mm)
Breaking Strength: 33,000 lbs (15,000kg)
Sleeve Color: Black
Sleeve Material: Nylon

Winch Ring
Winch Ring Material: T6 6061 Aircraft Grade Aluminum
Winch Ring Surface Finish: E-Coating
Diameter: 97mm
Compatible Rope Diameter: 10-14mm
Working Load: 17,637lbs (8,000kg)

OPERATION INSTRUCTIONS

- Run your synthetic winch rope around the exterior of the ring.
- Pass the soft shackle through the eyes of the recovery point and the ring.
- Open the eye of the soft shackle by sliding it along the rope and increasing the diameter sufficiently to pass over the knotted end.
- Slide the eye loop over the knotted end and then pull the eye loop tight around the shackle and snug against the knotted end to create a secure connection.
- Pull the winch rope back towards your vehicle and connect it to a rated recovery point.



WARRANTY

Fieryled ("Manufacturer") warrants to the original buyer ("User") that its Soft Shackle & Snatch Ring sold hereunder shall be free from material defects in workmanship or materials and conform to Fieryled's specifications for this product under normal application, connection, use and maintenance conditions from the date sold and for the duration (the "Warranty Period") of 1 YEAR.

If it fails to operate during the limited warranty period due to defects in materials or workmanship, Fieryled will, at its option, replace it with the same or similar product, or issue a refund.

This limited warranty is provided by Fieryled and there are no other warranties, expressed or implied, except as required by law, including warranties of merchantability and fitness for a specific purpose, that are provided for herein, however all such implied warranties, if any, are limited to the duration of this specific limited product warranty. Oral statements or representations about the product do not constitute warranties.

THIS WARRANTY WILL NOT APPLY IF:

- the product has been repaired, altered or modified;
- the alleged defect in the Product is within acceptable industry variances;
- Fieryled cannot establish any fault in the Product after testing and inspection;
- the Product has been used other than for the purpose for which it was designed;
- the defect in the Product has arisen due to the customer's failure to properly use and maintain the Product;
- the Product has been subject to abnormal conditions, including temperature, water, fire, humidity, pressure or similar;
- the defect has arisen due to abuse, misuse, neglect or accident.

CLAIMS:

No returns will be credited without an authorization. If a Fieryled product is suspected of being defective, you'll need to provide proof of purchase (e. g. a screenshot of the order) and a picture or video of the damaged goods in their entirety to the seller you purchased from for evaluation.

For more information, please visit <https://fieryled.com/>

