

COMPLETE RECOVERY KIT USER MANUAL



SKU: RECOVERY-KIT001A

V1.0



BUNKER INDUST, a disruptive force that aims to help people pursue their passions in the great outdoors with rugged looks and impeccable safety, is a professional provider of a full lineup of 4x4 upgrades and accessories that enable off-road enthusiasts to upgrade their vehicles and pursue an outdoor lifestyle.

At BUNKER INDUST, we regularly spend time outdoors to understand your desire to have an ideal rig. But that move is challenging and time-consuming. But it's what sets us apart. Because we are driven by enthusiasm, not commission, and share the same passion for vehicle upgrade as you do.

When you decide to build a vehicle to hit the trails, BUNKER INDUST is here to prepare it with virtually all the off-road parts required to keep you safe, and make sure your vehicle looks and performs as you want it to.

BUNKER INDUST, Build Your Own Legend.

IMPORTANT NOTE

WARNING INCORRECT USE MAY RESULT IN INJURY OR DEATH

Vehicle OCCUPANTS and BYSTANDERS have been KILLED by flying projectiles (such as tow balls) when recovery straps have been attached incorrectly. NEVER attach recovery straps to vehicle fittings such as tow balls, tow bars, tie-down points or tow hooks. ONLY attach recovery straps to an APPROVED recovery point/device that is suitably rated for use with the straps. BEFORE attempting a vehicle recovery all passengers must exit the vehicles and stand as far away as possible.



WARNINGS

- Exceeding the capacity of this product will cause it to fail. Do NOT use this product if it is damaged in any way and always inspect prior to use.
- Only use the snatch strap for the purpose it was designed for.
- Never use your strap for lifting or conventional towing.
- Persons intending to use this product should consider completing a nationally recognised four
 -wheel drive training course, or contact a four-wheel drive club for comprehensive advice on
 the proper selection and use of the recovery product.
- If you have any doubts about whether the recovery procedure is within the minimum breaking limit of your strap, DO NOT USE IT.
- It is recommended that the minimum breaking strength of the strap should be between 2 and 3 times the vehicle's gross vehicle mass.
- The strap must be suited to the gross vehicle mass of the lighter of the two vehicles used in the recovery process.
- Always drape an item such as a winch dampener, heavy bag, blanket or similar over your strap while in use.
- Be aware that a strap can lose up to 20% strength when wet.
- Do not tie knots with the snatch strap.
- Never over-tighten the shackle pin. Forces exerted on the shackle by vehicle recovery can cause the pin to seize. The correct method is to tighten the pin until it seats, then back off the pin approximately 1/2 to 1 full turn.

SAFETY

- Familiarise yourself with safe operating procedures before attempting to use the snatch strap.
- Never attempt to recover a vehicle without all the necessary equipment.
- All passengers should exit the vehicle. Passengers and spectators should stand more than 1.5 times the length of the recovery strap away from vehicles engaged in the recovery. Avoid standing in the path of the vehicle performing the recovery.
- Ensure good communication is maintained between participants and bystanders at all times. This is best achieved by use of UHF radio.



CONTENTS

1 PC(s) BUNKER INDUST Snatch Strap (30ft)
1 (Pair) BUNKER INDUST Bow Shackles
1 (Pair) BUNKER INDUST Bow Shackle Isolators
1 PC(s) BUNKER INDUST Hitch Receiver
1 PC(s) BUNKER INDUST Hitch Lock
2 PC(s) BUNKER INDUST Tubular Keys
2 PC(s) BUNKER INDUST Hitch Pin Clips
1 PC(s) BUNKER INDUST Carry Bag

SPECIFICATIONS

Snatch Strap: 30ft Snatch Strap Width: 3in Snatch Strap Color: Neon Orange Bow Shackle Color: Neon Orange/Black Hitch Receiver Color: Black Hitch Lock Color: Black Carry Bag Color: Black Snatch Strap Material: Polyester Snatch Strap Sleeve Material: Polyester Bow Shackle Material: PVC Coated Forged Iron Bow Shackle Isolator Material: PP Hitch Receiver Material: PVC Coated Forged Iron Hitch Lock Material: PVC Coated Forged Iron Carry Bag Material: Oxford Fabric Breaking Strength (Snatch Strap): 32,000lbs (Single) Maximum Load Capacity (Bow Shackle): 4.75T (Single) Maximum Load Capacity (Hitch Receiver): 4.75T (Single)





USING THE SNATCH STRAP

The method for using a snatch strap is quite simple; however, improper use can cause serious damage or injury.

- The recovery vehicle should be placed within reach of the snatch strap and if possible directly
 in line with the direction of pull. If this is not possible due to insufficient length, two straps may
 be joined using the correct method. Never join snatch straps with a bow shackle, as this may
 become a lethal missile in the event of strap breakage.
- The strap should be unrolled and connected to an approved recovery point on each vehicle with a bow shackle ensuring that the strap is not twisted. Approximately 2~3m of slack strap should be left between the vehicles. NEVER attach recovery straps to vehicle fittings such as tow balls, tow bars, tie-down points or tow hooks.
- Fix an item such as a winch dampener, heavy bag, blanket or similar to the strap approximately mid-way between the vehicles.
- Clear all bystanders from the recovery area to a safe distance.
- With communications maintained between both vehicles, the recovery vehicle should gently
 accelerate to take up the slack and proceed on, allowing the strap to pull out the stranded
 vehicle. For best results the stranded vehicle can assist by trying to drive at the same time. If
 the vehicle is not recovered on the first attempt, a little more speed by the recovery vehicle
 may be needed.
- Once free, the recovered vehicle should take care not to run over the snatch strap as damage to the strap may occur.
- Only once both vehicles are stationary and secured should the snatch strap be removed.
 NOTE: Be aware that the recovery strap will be under greater load if the vehicle is bogged in mud, sand or is heavily laden.





USING THE HITCH LOCK

- 1. Insert and turn the key to unlock and separate the hitch lock.
- 2. Insert the hitch lock into the receiver hole. Push the lock head onto it and lock in place.
- 3. For extra safety, insert the pin clip into the pin hole.



GENERAL CARE AND MAINTENANCE

- Inspect the entire length of any strap for nicks and cuts before and after use. If damaged, the strap may fail and should be replaced.
- Avoid kinks and twists in the webbing & keep clear of all sharp and hot surfaces.
- Inspect all bow shackles for damage. Pins that are hard to turn suggest that the shackle has been overstressed and should be replaced.
- Clean your straps in warm water with a mild detergent and allow to dry thoroughly before storage. The ingress of foreign material such as sand and grit can permanently damage the fibres of the strap.
- Never pressure wash snatch strap.
- Always coil your straps during storage.
- When storing, ensure strap is completely dry and not stored in direct sunlight or wet/humid environment.
- Please cap the key slot of the lock after use.
- Please keep your spare key and spare pin clip in a discreet location for emergencies.



WARRANTY

BUNKER INDUST warrants that each complete recovery kit that is purchased while this Warranty is in effect will be free from defects in materials and workmanship for a period of 1 year from the date of receiving the product from BUNKER INDUST or its authorized distributor /dealer. If it is believable to be defective during the 1-Year Warranty Period, BUNKER INDUST will, at its option, replace it with the same or similar product or will issue a refund for the defective BUNKER INDUST product.

And BUNKER INDUST will pay for the cost of shipping or transportation of a defective component.

This warranty terminates if a purchaser transfers the product to any other person. And please retain your purchase receipt for your records.

Please ensure that the BUNKER INDUST complete recovery kit should be used and maintained in accordance with warnings listed in the user manual, and should be used for the purpose for which it was designed.

THIS LIMITED WARRANTY DOES NOT COVER:

- normal wear and tear;
- fitting the product other than in accordance with the product information and any relevant vehicle safety and compliance laws, including incorrect fitting;
- using the product other than for the purpose for which it was originally designed or other than in accordance with the product information and any relevant vehicle safety and compliance laws, including unusual, improper or negligent use or misuse or overloading;
- improper repair or maintenance or failing to repair or maintain;
- alteration, abuse, acts of nature, terrorism, vandalism, collision, road hazards or adverse conditions.

If further information or investigation is required or if the claim does not meet the requirements under our warranty, BUNKER INDUST'II let you know.