SunWave™

PAR30 Dimmable

Yuji Lighting[®] SunWaveTM LED lamps provide optimal lighting solutions for the perfect simulation of sunlight. Designed with Yuji solar spectrum technology, lamps emit nearly 100% similar solar spectrum, giving people the same experience as sunlight. They are excellent for all scenarios that require artificial light sources, such as hospital, classroom, office, studio, apartment etc.



Features











- · Up to CRI 98+ light quality
- · Up to R9 95+ improved skin tone rendering
- TM30 & TLCI specified & controlled
- · Flicker free with maximum 8% fluctuation depth
- · Soft warm light for eye comfort
- · 30,000 hours life time
- · Smooth dimming down to 5%
- Heavy-duty design

Specification

| Part Number | Power Consumption | CRI | Beam Angle | Color- Temp | Luminous Flux | ON/OFF | Lifetime |
|----------------|----------------------|-----|---------------|----------------|------------------|---------|----------|
| L3210207/08.27 | | | | 2700K | 1600lm | | |
| L3210207/08.30 | | | | 3000K | 1600lm | | |
| L3210207/08.40 | 20W | 98+ | 24°/60° | 4000K | 1800lm | 100,000 | 30,000h |
| L3210207/08.50 | | | | 5000K | 1800lm | | |
| L3210207/08.65 | | | | 6500K | 1800lm | | |

SunWave™ PAR30 Dimmable

| General Information | | | |
|---------------------|--------|----------------------|----------|
| Cap base: | E27 | Nominal lifetime: | 30000 h |
| EU RoHS compliant: | Yes | Switching cycle: | 100000 X |
| Diameters: | 95 mm | Net weight per lamp: | 370 g |
| Height: | 127 mm | | |

| Technical data—Photometrical | | | | |
|------------------------------|-------------------|------------------------|-----|--|
| Color-Temp: | 2700K ~ 6500K | Color rendering index: | 98+ | |
| Initial luminous flux: | 1600 lm ~ 1800 lm | R9: | 90+ | |
| Color consistency: | SDCM<6 | TM-30-20 Rf: | 96 | |
| Beam angle: | 24° / 36° | TM-30-20 Rg: | 101 | |

| Technical data—Electrical | | | | |
|---------------------------|--------|----------------------|-----------|--|
| Power: | 20 W | Nominal voltage: | 220~240 V | |
| Power factor: | ≥ 0.95 | Input frequency: | 50/60 Hz | |
| Lamp current: | 90 mA | Starting time: | <0.5 s | |
| Dimmable: | Yes | Warm-up time (60 %): | <0.5 s | |

