


086 SERIES, SEMI-FLEX CABLE ,
2.92MM(MALE)- GPPO(MINI-SMP)(FEMALE)

GA711-292MGPPWF-XXX



* Label and Shrinking tube design depend on customer's request.

Configuration

| | |
|---------------------------|----------------------------|
| Connector 1 Type | 2.92mm Male |
| Connector 1 Body Style | Straight |
| Body Material and Plating | Passivated Stainless Steel |
| Connector 1 Mount Method | None |
| Connector 2 Type | GPPO(Mini-SMP) Female |
| Connector 2 Body Style | Right Angle |
| Body Material and Plating | CuBe Gold Plated |
| Connector 2 Mount Method | None |
| Cable Type | UT-085-Form |

Electrical Specifications

| | |
|-------------------------|---------------------------------------|
| Impedance | 50 Ω |
| Frequency | DC to 40GHz |
| Return Loss/VSWR | 10dB to 40 GHz |
| Shielding Effectiveness | <-125dB @ 1GHz |
| Phase Matching | On Request |
| Signal Delay | On Request |
| Power Handling | 141.4Watt @ 1GHz at Sea Level,VSWR1.0 |

Environmental Data

| | |
|-------------------|-----------------|
| Temperature Range | -45°C to +125°C |
| RoHS | Compliant |

086 SERIES, SEMI-FLEX CABLE ,
2.92MM(MALE)- GPPO(MINI-SMP)(FEMALE)

GA711-292MGPPWF-XXX

Cable Specifications

| | |
|----------------------------|----------------------|
| Center Conductor | Silver plated copper |
| Dielectric | Solid extruded PTFE |
| Outer Conductor | Tin Plated Braid |
| Capacitance(pF/m) | 95.2 |
| Velocity of propagation(%) | 70 |
| Min. bending radius(mm) | 6 |
| Jacket Diameter(mm) | 2.2 |
| Weight(kg/100m) | 1.7 |

Part Number List

| Part Number | Length [mm] | Insertion Loss ≤(dB) | | | |
|----------------------|-------------|----------------------|-------|-------|------|
| | | 3GHz | 10GHz | 18GHz | 40G |
| GA711-292MGPPWF-1000 | 1000±10 | 1.33 | 2.71 | 3.65 | 6.92 |
| GA711-292MGPPWF-500 | 500±10 | 0.785 | 1.42 | 2.15 | 3.82 |
| GA711-292MGPPWF-300 | 300±10 | 0.53 | 0.96 | 1.49 | 2.56 |
| GA711-292MGPPWF-200 | 200±5 | 0.404 | 0.74 | 1.16 | 1.94 |
| GA711-292MGPPWF-100 | 100±5 | 0.27 | 0.52 | 0.83 | 1.32 |

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.