



* Label and Shrinking tube design depend on customer's request.

Configuration

Connector 1 Type	N Male
Connector 1 Body Style	Straight
Body Material and Plating	Brass Nickel Plated
Connector 1 Mount Method	None
Connector 2 Type	SMA Female
Connector 2 Body Style	Straight
Body Material and Plating	Brass Gold Plated
Connector 2 Mount Method	4 Hole Flange
Cable Type	GUT-141-Form-FEP

Electrical Specifications

Impedance	50 Ω
Frequency	DC to 6GHz
Return Loss/VSWR	1.35 to 6GHz
Shielding Effectiveness	<-100dB @ 1GHz
Phase Matching	On Request
Signal Delay	On Request
Power Handling	182Watt @ 5GHz at Sea Level,VSWR1.0

Environmental Data

Temperature Range	-45°C to +125°C
RoHS	Compliant

Cable Specifications

Center Conductor	Silver plated copperweld
Dielectric	Solid PTFE
Jacket	FEP
Capacitance(pF/m)	95.1
Velocity of propagation(%)	70
Min. bending radius(mm)	10
Jacket Diameter(mm)	4.6±0.13

Part Number List

Part Number	Length [mm]	Insertion Loss ≤(dB)	
		3GHz	5GHz
GA722-NMSMFF-1000	1000±10	0.48	1.11
GA722-NMSMFF-800	800±8	0.41	0.93
GA722-NMSMFF-600	600±6	0.33	0.75
GA722-NMSMFF-500	500±5	0.29	0.655
GA722-NMSMFF-400	400±5	0.255	0.56
GA722-NMSMFF-300	300±5	0.22	0.47
GA722-NMSMFF-260	260±5	0.198	0.436
GA722-NMSMFF-200	200±5	0.176	0.382
GA722-NMSMFF-100	100±5	0.138	0.291

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.