


RG316,FLEXIBLE CABLE ,
SMA(MALE)- SMA(MALE)

GAR3-SMMSMWM-XXX



* Label and Shrinking tube design depend on customer's request.

Configuration

Connector 1 Type	SMA Male
Connector 1 Body Style	Straight
Body Material and Plating	Brass Gold Plated
Connector 1 Mount Method	None
Connector 2 Type	SMA Male
Connector 2 Body Style	Right Angle
Body Material and Plating	Brass Gold Plated
Connector 2 Mount Method	None
Cable Type	RG316

Electrical Specifications

Impedance	50 Ω
Frequency	DC to 3 GHz
Return Loss/VSWR	1.30
Shielding Effectiveness	<-60dB @ 1GHz
Power Handling	88watt @ 1.5GHz at sea level,VSWR1.0

Environmental Data

Temperature Range	-45°C to +125°C
RoHS	Compliant

RG316,FLEXIBLE CABLE ,
SMA(MALE)- SMA(MALE)**GAR3-SMMSMWM-XXX****Cable Specifications**

Center Conductor	Silver plated copper
Dielectric	Solid extruded PTFE
Outer Conductor	FEP
Capacitance(pF/m)	94
Velocity of propagation(%)	70
Min. bending radius(mm)	15
Jacket Diameter(mm)	2.45
Weight(kg/100m)	1.5

Part Number List

Part Number	Length [mm]	Insertion Loss ≤(dB)	
		1GHz	3GHz
GAR3-SMMSMWM-5000	5000±20	4.65	7.85
GAR3-SMMSMWM-2000	2000±20	1.95	3.25
GAR3-SMMSMWM-1000	1000±10	1.05	1.75
GAR3-SMMSMWM-500	500±10	0.65	1.04

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.