



2.4mm FEMALE

1.0mm FEMALE

\* Label and Shrinking tube design depend on customer's request.

<b>Configuration</b>	
Connector 1 Type	2.4mm Female
Connector 1 Body Style	Straight
Body Material and Plating	Passivated Staindless Steel
Connector 1 Mount Method	None
Connector 2 Type	1.0mm Female
Connector 2 Body Style	Straight
Body Material and Plating	Passivated Staindless Steel
Connector 2 Mount Method	None
Cable Type	U12 Series
<b>Electrical Specifications</b>	
Impedance	50 $\Omega$
Frequency	DC to 50 GHz
Return Loss/VSWR	1.35 to 50 GHz
Phase Stability vs. Flexure	N/A
Amplitude Stability	N/A
Shielding Effectiveness	<-90dB @ 1GHz
Phase Matching	On request
Signal Delay	On request
<b>Environmental Data</b>	
Temperature Range	-40°C to +125°C
2002/95/EC(RoHS)	Compliant

**Cable Specifications**

Center Conductor	Silver plated copper
Dielectric	ePTFE
Jacket	FEP
Velocity of propagation(%)	80
Min. bending radius(mm)	10
Jacket Diameter(mm)	1.85

**Armor Specifications**

Armor Type	Stainless steel wire covered by Tin plated copper wire and nomex braid
Min. bending radius(mm)	25.4
Diameter(mm)	7.5

**Part Number List**

Part Number	Length [mm]	Insertion Loss ≤(dB)				
		6GHz	18GHz	26.5GHz	40GHz	50GHz
GAU12-24F10F-1000A3	1000±10	2.96	5.21	6.38	7.93	8.92
GAU12-24F10F-800A3	800±10	2.39	4.21	5.15	6.40	7.21
GAU12-24F10F-600A3	600±5	1.82	3.21	3.93	4.88	5.50
GAU12-24F10F-400A3	400±5	1.26	2.21	2.71	3.36	3.78
GAU12-24F10F-200A3	200±5	0.69	1.22	1.49	1.84	2.07

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.