

Cable Specifications

Center Conductor	Silver plated copper
Dielectric	ePTFE
Jacket	FEP
Capacitance(pF/m)	94
Velocity of propagation(%)	82
Min. bending radius(mm)	6
Jacket Diameter(mm)	2.2

Part Number List

Part Number	Length [mm]	Insertion Loss \leq (dB)			
		3GHz	5GHz	10GHz	18GHz
GAU2-SMMSMM-10000	10000 \pm 50	13.2	16.5	24.5	29.8
GAU2-SMMSMM-1000	1000 \pm 10	1.4	1.7	2.5	3.35
GAU2-SMMSMM-800	800 \pm 8	1.16	1.4	2.06	2.83
GAU2-SMMSMM-500	500 \pm 5	0.785	0.95	1.42	1.94
GAU2-SMMSMM-300	300 \pm 5	0.53	0.65	0.96	1.36
GAU2-SMMSMM-260	260 \pm 5	0.48	0.59	0.87	1.22
GAU2-SMMSMM-200	200 \pm 5	0.404	0.51	0.74	1.06
GAU2-SMMSMM-100	100 \pm 5	0.27	0.35	0.52	0.75

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.