



For glass-bead of 0.51mm pin diameter

*Dimensions are in mm

Configuration

| | |
|----------------------------|---------------------|
| Connector 1 Type | SMA Male |
| Connector 1 Impedance | 50 Ohms |
| Connector 1 Polarity | Standard |
| Body Style | Straight |
| Connector Mount Method | 2 Hole Flange |
| Connector 2 Interface Type | Jack for 0.51mm Pin |
| Attachment Method | Contact |

Electrical Specifications

| | |
|---------------------|--|
| Frequency | DC to 26.5 GHz |
| Insertion Loss (dB) | $\leq 0.1 \times \text{Sqrt.}(f_GHz)$ |
| Return loss/VSWR | 1.15 |

Materials Information

| | |
|----------------|------------------|
| Centre Contact | CuBe Gold Plated |
| Outer Contact | Stainless Steel |
| Body | Stainless Steel |
| Dielectric | PEI & PTFE |

Environmental Data

| | |
|-------------------|-----------------|
| Temperature Range | -55°C to +165°C |
| 2002/95/EC(RoHS) | Compliant |

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.