

User's Manual







www.rbrohant.com

INSTALLATION INSTRUCTIONS

Installation Manual









INSTALLATION STEPS



blocking the faucet.



1.Installation Steps of Valve Body

1). According to the product, set the proper height and correct position of the installation. (Please double check, especially the correct space between the wall and valve trim plate.)



2). Dimensions of the embedded box for dual-function shower set



3). Put the product body into the pre-embed slots and be close to the bottomplane of the groove. Check the level meter that comes with the product, and adjust the bottom of the groove so that the air ball in the level can be in the horizontal line.



Level meter magnified view

INSTALLATION STEPS

4). Punch 4 holes in the pre-embed slots (Ø=0.24", depth=0.31").



7). Secure the valve body in the slot with self-tapping screws and connect the cold and hot inlet pipes: (Note: left/HOT; right/COLD.)



10). Unscrew the screws and remove the plastic shield.



5). Drive expansion sleeves into the 4 holes.

8). Check that the pipe

connections are free of

leaks. Then seal the

pre-buried valve with

cement concrete, tiled

The water outlet joint of shower head. If the style

Ø

the wall.

6). Connect the cold and hot inlet pipes, top shower outlet pipe/hand spray pipe and the adapters in order. Note: the thread connection should be wrapped with Teflon tape.



9). Triple check before you tile the wall. Make sure the correct space is reserved for the control box and the water outlet. The control box should be flush with the tile surface when the tile is finished.



11). Install the panel

and handles in order.



INSTALLATION STEPS

2.Installation Steps of Rain shower

1). Attach the cover plate to the longer tail of the shower arm.

2). Shower arm longer thread with Teflon tape. 3. Screw the shower head clockwise onto the lower end of the shower pipe.



3.Installation Steps of Hand Shower

1). Wrap supply elbow thread with Teflon tepe and attach cover plate to it.

2). Screw the shower holder clockwise onto the hand-shower outlet.











CLEANING CARE

In order to keep the appearance of faucet clean, bright and good performance, please take care of the faucet as follows; 1. Rinse with water only and dry with soff cotton cloth;



2.Use mild liquid and colorless glass cleaner to remove surface dirt and scale film, or use polish without abrasive effect; 3.Do not use abrasive deterfgent, polish, emery cloth, paper towel or scraper, etc.;

4.Do not use acid cleaner, or cleaner and soap with insoluble gran etc.;

5.In the process of use, mud my accumulate in the bubbler and make the water flow show, The bubbler can be unscrewed, rinsed with water, and then installed back in place.



Service Contact:

+1(801) 800-9309 services@rbrohant.com

Please feel free to contact us if you have any questions. We will help to solve the issue together with you. OUR EMAIL: services@rbrohant.com

Made in China