LED Parking Lot Light



Product Description

Eagle Star led Parking Lot light is the perfect option for outdoor area lighting where security and safety is paramount. They replace the traditional Carpark/Court light and add the efficiency of LED technology while maintaining form, fit and function. Constructed of die-cast aluminium is IP66 waterproof, mounting variations and wide range of power options they replace and enhance upon the facility provided by their traditional HID fixture.



- Voltage 100-277V&277-480V AC 50/60Hz
- PHILIPS LEDS with efficiency 140lm/w
- Lifespan above 50,000 hours
- Qualified with CE, RoHS, cETL, ETL, DLC
- 5 years warranty

Product Parameters

• IP 66

- UL LED driver PF > 0.95, THD < 10%,12KV surge protector
- IES Type III distribution patterns
- Brown Finish
- Optics are interchangeable and easily replaceable
- Dusk to dawn sensor & motion sensor compatible
- Ambient temperature from -40°C to 40°C

| Input power | 100W | 150W | 200W | 240W | 300W | 450W |
|---------------------|------------------------------------|---------------|--------------|-------------|-------------|-------------|
| LED Chips | PHILIPS LEDS | | | | | |
| Lumens | 14,000lm | 21,000lm | 28,000lm | 33,600lm | 42,000lm | 63,000lm |
| Efficiency | 140lm/w | 140lm/w | 140lm/w | 140lm/w | 140lm/w | 140lm/w |
| CRI | > 75Ra | | | | | |
| ССТ | 5000k | | | | | |
| Beam angle | type III | | | | | |
| Input voltage | 100-277V & 277-480VAC 50/60Hz | | | | | |
| Working temperature | -40°C Up to 40°C (-40°Fup to104°F) | | | | | |
| Certification | CE, RoHS, cETL, ETL, DLC | | | | | |
| Warranty | 5 years | | | | | |
| Replacement | 300W | 480W MH | 600W MH | 800W MH | 1000W MH | 1500W |
| Piece/Carton | 1 | 1 | 1 | 1 | 1 | 1 |
| G.W | 6.6kg | 6.7kg | 8.3kg | 8.5kg | 8.6kg | 12.5kg |
| Carton Size | 60 *40 *18 cm | 60 *40 *18 cm | 70*40 *18 cm | 70*40*18 cm | 70*40*18 cm | 83*40*18 cm |

Goods are shipped from CA NY TX Warehouses in the USA. Email: info@eaglestarled.com. https://eaglestarled.com/collections/led-parking-lot-light

Dimensions



Goods are shipped from CA NY TX Warehouses in the USA. Email: info@eaglestarled.com. https://eaglestarled.com/collections/led-parking-lot-light

Installation

1.Slip fitter mount (Adjustable Angle : $-90^{\circ} \rightarrow +90^{\circ}$)

4. Wall Mount (Adjustable Angle: -90° ~+90°)





2. Adjustable Square (Adjustable Angle : $-90^{\circ} \rightarrow +90^{\circ}$)

5.Trunnion (Adjustable Angle : $-90^\circ~~\text{+}90^\circ$)



3.Round Pole Mount(Adjustable Angle : -90° ~+90°)



6. U-bracket (Adjustable Angle : -90° ~+90°)

