

0204 1xN Coupler Array

C9509-S



1x5 1310 nm & 1550 nm Tap Coupler Module, Tap Ratio: TERM, Coupler Ratio: 50/50

The module is a 1x5 1310 nm & 1550 nm tap coupler module, tap ratio: TERM, coupler ratio: 50/50. This highly reliable coupler module offers very low insertion loss, low polarization dependence and excellent environmental stability.

FEATURES

- Low Excess Loss
- Low Insertion Loss
- Low PDL
- High Stability and Reliability

USE IN

- Optical Communication
- Local Area Network
- FTTH & LAN
- HFC & Fiber Sensors

Operating Wavelength	1310 nm & 1550 nm
Dimensions	111.125x50.8x12.7 mm
Port Configuration	1x5
Fiber Type	SM-28e with 900 μm Loose Tube
Operating Temperature	-45°C to 80°C

Wavelength Tested: 1310 nm

Input 1	Red	White	Black	Blue	○
Insertion Loss	6±0.5 dB	6±0.5 dB	6±0.5 dB	6±0.5 dB	
Loss Variation at Output Ports	0.2 dB max.				
Excess Loss	0.1 dB max.				

Wavelength Tested: 1550 nm

Input 1	Red	White	Black	Blue	○
Insertion Loss	6±0.5 dB	6±0.5 dB	6±0.5 dB	6±0.5 dB	
Loss Variation at Output Ports	0.2 dB max.				
Excess Loss	0.1 dB max.				

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

1) Connector FC/APC, 900 μm, 1 m by default for all devices except for high power devices.

2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.