

DF1005



I-12(980/125)

Erbium Doped Fibers (EDFs) offer a wide selection of absorption and cut-off wavelengths to allow the best choice of fiber for each type of Erbium Doped Fiber Amplifier(EDFA) design. Low absorption fibers offer best-in-class efficiency for C-band amplifiers whilst higher absorption fibers are optimized for L-band EDFAs. The core composition of Fibercore’s IsoGain™ has been engineered to generate a substantially flattened wavelength response that closely matches that of other leading fiber types.

Optical Fiber

Optical Fiber

FEATURES

- High Efficiency Core Composition
- Wide Range of Absorption Values
- High Absorption Fibers

USE IN

- EDFAs / Telecoms
- ASE Light Sources
- Fiber Lasers
- Biomedical Illumination
- Optical Coherence Tomography

Cut-Off Wavelength	900 nm to 970 nm
Absorption	14 to 21 dB/m@1531 nm
Numerical Aperture	0.21 to 0.23
Mode Field Diameter	5.7 μm to 6.6 μm@1550 nm
Core Concentricity	0.3 μm max.
Cladding Diameter	125.0±1.0 μm
Coating Diameter	245.0±15.0 μm
Coating Material	Dual Coated High Index Acrylate
Proof Test	100 kpsi min.