

# 1206 Connector



## FC UPC Premium Connector

### FEATURES & USE IN

- Highest Quality Premium Connector Series
- Designed to Exceed the Requirement of Verizon FOC TPR 9409 Requirement
- Premium Low Loss SM, typ. IL Against Master 0.05 dB
- Premium Low Loss to Meet IEC 61753-1 Grade A Random Mating Requirement of max. 0.15 dB
- Premium SM typ. IL Against Master 0.08 dB
- Premium SM to Meet IEC 61753-1 Grade B Random Mating Requirement of max. 0.25 dB
- 4 Directions Tuning Ferrule to Improve Random Mating IL
- Crimp Tool to Be Used CRT-401
- Narrow Key Width 2.00±0.02 mm

### ORDERING OPTIONS

Connector	351	Premium
	103	SM: Premium 125 µm
Ferrule Type	109	SM: Low Loss 125 µm
	201	MM: Premium 127 µm
	7	Long 3.0 mm
	A	Long 2.0 mm
	M	Standard 900 µm
	N	Standard 2.0 mm
Boot Type	P	Standard 3.0 mm
	J	<b>MINI 900 µm</b>
	K	<b>MINI 2.0 mm</b>
	L	<b>MINI 3.0 mm</b>
	F	Flex Angle Boot 3.0 mm
	1	Blue
	2	Black
	3	Green
Boot Color	4	Red
	6	Yellow
	7	White
	8	Beige
	9	Aqua

Note: Other ferrule ID size are available, SM 81 µm, SM 125.5 µm, MM 230 µm, MM 144 µm