

# 1306 Connector

FCC1001



## FC APC Premium Connector

### FEATURES

- Highest Quality Premium Connector Series
- Designed to Exceed the Requirement of Verizon FOC TPR 9409 Requirement
- Premium Low Loss SM, typ. IL Against Master 0.07 dB
- Premium SM typ. IL Against Master 0.08 dB
- Cone Ferrule Type and Step Ferrule Type Available
- Option of an 8 Degree Pre-angle Cut Available
- Various Choices of Boots Types
- Crimp Tool to Be Used CRT-401
- Narrow Key Width  $2.00 \pm 0.02$  mm

### ORDERING OPTIONS

Order Options	Order Cord	Description
Connector	292	Premium Step
	293	Premium Cone
Ferrule Type	203	SM: Premium 125 $\mu$ m
	209	SM: Low Loss 125 $\mu$ m
Ferrule Polish	1	No Angle
	2	8° Pre-Angle
	7	Long 3.0 mm
Boot Type	A	Long 2.0 mm
	M	Standard 900 $\mu$ m
	N	Standard 2.0 mm
	P	Standard 3.0 mm
	J	MINI 900 $\mu$ m
	K	MINI 2.0 mm
	L	MINI 3.0 mm
	F	Flex Angle Boot 3.0 mm



Cone Ferrule



Step Ferrule



900 $\mu$ m MINI Boot



2.0mm MINI Boot



3.0mm MINI Boot

Note: Other ferrule ID size are available. SM 81 $\mu$ m, SM126  $\mu$ m, SM 125.5 $\mu$ m

**Order notes to our customers:** The default parameters are as follows. For special needs, please contact sales.

**1) Connector FC/APC, 900  $\mu$ m, 1 m by default for all devices except for high power devices.**

**2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.**