

0802 Electro-Optic Bias-Free Modulator

IM-BF1000



Bias-Free, with SMA Connector Intensity Modulator, 3 GHz Bandwidth

The 3 GHz bias-free intensity modulator is housed in a compact package. The bias point of the Mach Zehnder Interferometer (MZI) is set to operate at the half-intensity point (quadrature). Due to this unique design, a complicated bias control circuit is not required. The modulator provides superior signal quality over a wide range of wavelength in the C and L-bands. This modulator can be used to modulate unpolarized light source such as: tunable lasers and ASE sources. These devices have a bandwidth of >3 GHz that can be used for both analog modulation, optical pulse generation, and digital data modulation. This device is built with proton exchange waveguide, so it contains a built in polarizer. A high bandwidth PCB with SMA connector is included.

FEATURES

- Bias-free Operation for Fast Transmitter Development and Manufacturing
- Built-in 20 dB Variable Optical Attenuator
- Single Package for Less Splicing, Lower Overall Insertion Loss and More Usable Board Space
- 1535 nm to 1565 nm Operation, L-band Versions Available
- Low Drive Voltage, Compatible with Commercial Drivers
- Low Chirp for max. Transmission Distance (1000 km min.)
- Voltage-controlled Lithium Niobate Attenuator Provides Proven High Reliability

USE IN

- Medium and Long-haul DWDM Transmission Requiring Dynamic Optical Power Leveling
- Transmitters with Limited Component Space

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.
1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.
2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.

0802 Electro-Optic Bias-Free Modulator

IM-BF1000

Waveguide Process		Proton Exchange (PE) + Titanium Indiffused (TI)
Integrated Photodiode		No
Operating Wavelength Range		1530 nm to 1610 nm
Insertion Loss		4 dB typ.
On/Off Extinction Ratio		27 dB typ.
Optical Return Loss		45 dB min.
Drive Voltage V _{pi}		3.2 V typ.
Electro-optic-bandwidth (-3 dB)		3.0 GHz typ.
RF Return Loss	RF Port	10 dB min. from 0.03 GHz to 3 GHz
RF Input Power		24 dBm
RF Impedance		50 Ohm
Drive Voltage V _{pi}	Bias Port	NA, Bias Free
Input Impedance		NA
Input Fiber		PANDA-900 micron Loose Tube
Output Fiber		SMF-28-900 micron Loose Tube
Input Connector		FC/UPC (PM)
Output Connector		FC/UPC
RF Connector		SMA
Bias Connector		NA
Dimension		24x63x19 mm
Operating Temperature Range		0°C to +70°C
Storage Temperature Range		-40°C to +80°C

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.
1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.
2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.