

## LCC1000



### LC Premium Unibody Connector Type 1

#### FEATURES & USE IN

- Solid Body Robust Design to Improve Mechanical Strength
- Designed to Exceed the Requirement of Verizon FOC TPR 9409 Requirement
- Premium Super Low Loss, typ. IL Against Master 0.05 dB
- Premium Super Low Loss to Meet IEC 61753-1 Grade A Random Mating Requirement of max. 0.15 dB
- Premium SM typ. IL Against Master 0.08 dB max.
- Premium SM to Meet IEC 61753-1 Grade B Random Mating Requirement of max. 0.25 dB
- 6 Direction Tuning Feature to Improve Random Mating IL
- Wide Choice of Boot Types
- Crimp Tool to Be Used CRT-701
- Highest Quality LC Connector Series

#### ORDERING OPTIONS

Connector	931	LC Unibody Simplex	
	932	LC Unibody Duplex	
Ferrule Type	153	SM: Premium 125 µm	
	159	SM: Low Loss 125 µm	
	251	MM: Premium 127 µm	
Housing	1	SM: Blue	
	2	MM: Beige	
	5	MM OM3: Aqua	
	6	MM OM4: Heather Violet	
	B	MINI Boot 900 µm	
	C	MINI Boot 2.0 mm	
Boot Type	D	MINI Boot 3.0 mm	
	1	BTW Boot	
	4	2.0 mm Round	
	5	2.0 mm Boot Short	
	6	3.0 mm Boot	
	7	Flex-Angle 2.0 mm	
	9	Flex-Angle 3.0 mm	
	Boot Color	1	White
		2	Blue
3		Black	
4		Yellow	
5		Red	

Note: Other ferrule ID size are available  
SM 126 µm, SM 125.5 µm