

# 1206 Connector

SCC1000



## SC UPC Premium Connector

### FEATURES & USE IN

- Designed to Exceed the Requirement of Verizon FOC TPR 9409 Requirements
- Premium Low Loss SM, typ. IL Against Master 0.05 dB
- Premium Low Loss SM to Meet IEC 61753-1 Grade A Random Mating Requirement of max. 0.15 dB
- Premium SM typ. IL Against Master 0.08 dB
- Premium SM to Meet IEC 61753-1 Grade B Random Mating Requirement of max. 0.25 dB
- 4 Direction Tuning Feature to Improve Random Mating IL
- Crimp Tool to Be Used CRT-401
- Highest Quality Premium Connector Series

### ORDERING OPTIONS

Connector	254	Premium
Ferrule Type	193	SM: Premium 125 μm
	199	SM: Low Loss 125 μm
	291	MM: Premium 127 μm
Housing	5	Aqua
	6	Blue
	7	Black
	8	Red
	9	Beige
Boot Type	7	Long 3.0 mm
	A	Long 2.0 mm
	M	Standard 900 μm
	N	Standard 2.0 mm
	P	Standard 3.0 mm
	J	<b>MINI 900 μm</b>
	K	<b>MINI 2.0 mm</b>
	L	<b>MINI 3.0 mm</b>
Boot Color	F	Flex Angle Boot 3.0 mm
	G	Flex Angle Boot 2.0 mm
	1	Blue
	2	Black
	3	Green
	4	Red
	6	Yellow
	7	White
	8	Beige
9	Aqua	

Note: Other ferrule ID size are available, SM 81 μm, SM 125.5 μm, MM 230 μm, MM 144 μm