

1306 Connector

SCC1001



SC APC Premium Connector

FEATURES

- Highest Quality Premium Connector Series
- Designed to Exceed the Requirement of Verizon FOC TPR 9409 Requirement
- Premium Low Loss SM, typ. IL Against Master 0.07 dB
- Premium SM typ. IL Against Master 0.08 dB
- Cone Ferrule Type and Step Ferrule Type Available
- Option of an 8 Degree Pre-angle Cut Available
- Various Choices of Boots Types
- Crimp Tool to Be Used CRT-401

ORDERING OPTIONS

Order Options	Order Cord	Description
Connector	291	Premium Step
	294	Premium Cone
Ferrule Type	193	SM: Premium 125 μ m
	199	SM: Low Loss 125 μ m
Polish	1	No Angle
	2	8° Pre-Angle
Boot Type	7	Long 3.0 mm
	A	Long 2.0 mm
	M	Standard 900 μ m
	N	Standard 2.0 mm
	P	Standard 3.0 mm
	J	MINI 900 μ m
	K	MINI 2.0 mm
	L	MINI 3.0 mm
	F	Flex Angle Boot 3.0 mm
	G	Flex Angle Boot 2.0 mm



Cone Ferrule



Step Ferrule



900 μ m MINI Boot



2.0mm MINI Boot



3.0mm MINI Boot

Note: Other ferrule ID size are available SM 81 μ m, SM 125.5 μ m

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

1) Connector FC/APC, 900 μ m, 1 m by default for all devices except for high power devices.

2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.