

1106 LED UV

UVLED-1000

260 nm to 405 nm UVLED

Type 1: 260 nm LED UV



Wavelength Range	260 nm
Current	20 mA
Voltage	5.5 V to 6 V
Output Optical Power	1 mW
Vision Angle	7° to 120°

Type 2: 265 nm LED UV



Wavelength Range	265 nm to 270 nm
Current	20 mA
Voltage	5.5 V to 6 V
Output Optical Power	1 mW
Vision Angle	7° to 120°

Type 3: 270 nm LED UV



Wavelength Range	270 nm to 275 nm
Current	20 mA
Voltage	5.5 V to 6 V
Output Optical Power	1 mW
Vision Angle	7° to 45°

Type 4: 280 nm LED UV



Wavelength Range	280 nm to 285 nm
Current	20 mA
Voltage	5 V to 5.5 V
Output Optical Power	1 mW to 1.2 mW
Vision Angle	7° to 120°

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.

2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.

1106 LED UV

UVLED-1000

Type 5: 310 nm LED UV



Wavelength Range	310 nm to 315 nm
Current	20 mA
Voltage	5 V to 5.5 V
Output Optical Power	1 mW
Vision Angle	7° to 120°

Type 6: 320 nm LED UV



Wavelength Range	320 nm to 325 nm
Current	20 mA
Voltage	5 V to 5.5 V
Output Optical Power	1 mW
Vision Angle	7° to 120°

Type 7: 375 nm to 380 nm LED UV



Wavelength Range	370 nm to 375 nm to 380 nm
Current	20 mA
Voltage	3.2 V to 3.4 V to 3.6 V
Output Optical Power	6 mW to 7 mW
Vision Angle	22° to 45°

Type 8: 400 nm to 405 nm LED UV



Wavelength Range	395 nm to 405 nm
Current	20 mA
Voltage	3.2 V to 3.4 V to 3.6 V
Output Optical Power	10 mW to 15 mW
Vision Angle	25° to 60°

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.

2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.