



W3114-S

1X2 CWDM Device, 1550 nm

The WDM' W3114-S is a 1x2 CWDM device which can achieve line monitoring. It provides low insertion loss, high channel isolation, wide pass band, high stability and reliability and epoxy free optical path. It can be used for access network, WDM network, cellular application and fiber optical amplifier.

FEATURES

- Low Insertion Loss
- Wide Pass Band
- High Channel Isolation
- High Stability and Reliability
- Epoxy Free Optical Path

USE IN

- Line Monitoring
- WDM Network
- Telecommunication
- Cellular Application
- Fiber Optical Amplifier
- Access Network

Channel Wavelength	1550 nm	
Channel Spacing	20 nm	
Channel Passband (@-0.5 dB Bandwidth)	13 nm min.	
Pass Channel Insertion Loss	0.6 dB max.	
Isolation	Adjacent	30 dB min.
	Non-adjacent	40 dB min.
Reflection Channel Insertion Loss	0.4 dB max.	
Channel Ripple	0.3 dB max.	
Polarization Dependent Loss	0.1 dB max.	
Polarization Mode Dispersion	0.1 ps max.	
Return Loss	45 dB min.	
Power Handling	300 mW max.	
Directivity	50 dB min.	
Operating Temperature	-20°C to +75°C	
Storage Temperature	-40°C to +85°C	
Package Dimension	5.5x5.5x38 mm	