

Precipette™ Pipettes

ISO 8655

The ISO 8655 Calibrated Pipette with Autoclavable Lower Portion is an affordable, adjustable, autoclavable, and accurate pipette that is ISO 8655 calibrated and left-hander friendly? Yep, the Precipette Pipettes check a lot of boxes. These high-quality pipettes are ergonomic and budget friendly. If you have any questions about any of our liquid handling products do not hesitate to contact customer service or technical support regarding volume ranges, operation, service, and calibration.

Features

- Ergonomic design provides good hand grip, and combined with ultra-light weight offers fatigue-free pipetting
- Low operating force required for control button avoids repetitive strain injuries
- Ergonomically positioned ejector button with low plunger force for easy tip ejection
- Dispensing volume range of 0.1ul - 10ml
- Color codes on top to easily identify different volume ranges
- Large 4-digit volume display offers high display accuracy of up to 0.002ul
- Centrally placed view window makes volume reading and adjustment easy for both left and right-handers
- Elastic tip cone ensures perfect seal with tips and allows for easy tip removal
- Each pipette is calibrated in accordance with ISO8655 and shipped with individual test certificates
- Durable material offers excellent temperature and chemical resistance
- The lower section can be autoclaved
- Easy to dismantle, and maintain
- Comes with tool for easy calibration



4E's USA

A FOUR E'S SCIENTIFIC®
COMPANY

51 Everett Drive, Suite B-10
West Windsor, NJ 08550
Tel: 855.943.3344
Email: info@4Es-USA.com
Web: www.4Es-USA.com

Precipette™ Pipettes

ISO 8655

Specifications				
Model	Volume Range	Increment	Max. permissible systematic error (Inaccuracy)	Max. permissible random error (Imprecision)
LH0301001	0.1-2.0µL	0.002µL	2.50%	2.00%
LH0301002	0.5-10µL	0.01µL	1.00%	0.80%
LH0301003	2-20µL	0.02µL	0.90%	0.40%
LH0301004	5-50µL	0.05µL	0.60%	0.30%
LH0301005	10-100µL	0.1µL	0.80%	0.15%
LH0301006	20-200µL	0.2µL	0.60%	0.15%
LH0301007	100-1000µL	1µL	0.60%	0.20%
LH0301008	1000-5000µL	5µL	0.60%	0.15%
LH0301009	1-10mL	10µL	0.60%	0.20%

Color indicates color coding of pipette for quick determination of range



Pipette is supplied in Box with Manual, Calibration Certificate, Calibration Tool, Sample Pipette Tip, and Extra Pipette Lubrication for Disassembly, Autoclaving, and Cleaning.



4E's USA

A FOUR E'S SCIENTIFIC® COMPANY

51 Everett Drive, Suite B-10
West Windsor, NJ 08550
Tel: 855.943.3344
Email: info@4Es-USA.com
Web: www.4Es-USA.com