2208 ON METAL TAG

A popular and smaller size UHF Tag used on metal surfaces

It does a stable and reliable UHF on metal tag, which is widely used in indoor asset management.

ADVANTAGES:

- Be of good RF performance, work stably on metal surface.
- 4 100% memory writing tested.
- Both material and design have been tested for reliability.
- 100% function tested by Voyantec Tagformace.

MAIN FEATURES:

- Can customize size for customers.
- Flexible and convenient installation.
- Painted ones can be used in outdoor

APPLICATIONS:

- Tool management.
- IT equipment management.
- Metal containers management.
- Hetal equipment management.
- Personnel patrol management.
- Fixed asset management.



CHARACTERISTICS:

Compliance	EPC Class1 Gen2; ISO18000-6C
Frequency	902-928MHz , 865~868MHz (Can
	customize frequency)
Chip	NXP UCODE 7M (Can customize tag with
	different UHF chips,IMPINJ m4QT))
Memory	EPC 128bits (M4QT Chip)
	EPC 96 bits (Ucode7M Chip)
Read/write	Yes (EPC and User)
Data Storage	50 years
Warranty	One year
Material	FR4
Dimension	22mm*8mm*3mm(M4QT Chip)
	22mm*8mm*2mm(Ucode7M Chip)
Storage Temperature	-30 ℃~ +110 ℃
Operating Temperature	-25 ℃~ +85℃
Storage humidity	5%~95%
Delivery format	Single
Installation Method	3M300LSE tape (standard)
Weight	~ 1g
Package	Bubble bag and carton
Color	Black
Power Supply	Passive
Drop Test	1 meters high, 200 drop test passed
Alcohol test	95% alcohol test passed
Gasoline test	Passed
High & low temperature	-40 $^{\circ}$ C ~ +150 $^{\circ}$ C, 7 cycles, total 48 hours
shock test	
Temperature cycle test	-40 $^\circ\!\mathrm{C}$ \sim +120 $^\circ\!\mathrm{C}$, 7 times cycle time testing,
	48 hours total
RoHS	Compatible
Read distance on metal	Up to 1.2 meter (EIRP=4W)
surface	Up to 0.5 meters (With ATID AT880
	handheld reader)
RF performance	100% tested by Voyantic Tagformace
consistency test	
Options	pre-encoding. Surface painting