

## P2.5 Indoor 320\*160mm LED Module Specification


Model No.: **P2.5-I32S-SMD2121-128x64**


### LED Lamp Specification



Color	Package	Intensity	Viewing Angle	Wavelength	Testing Conditions
Red	SMD2121	80-104mcd	110°	618-623nm	25°C,15mA
Green		270-338mcd	110°	515-519nm	25°C,10mA
Blue		31-39mcd	110°	465-469nm	25°C,5mA

### Module Photo





### Module Parameter

Pixel Pitch	2.5mm
Pixel Configuration	SMD2121
Density	160,000 pixels/m <sup>2</sup>
Module Resolution	128pixel(L) * 64pixel(H)
Module Dimension	320mm(L) * 160mm(H) * 18mm(D)
Driving Mode	Constant current, 1/32 duty

### Electricity Parameter

Optical Ratings	
Brightness	≥1,000 cd/m <sup>2</sup>
Viewing Angle	140 °(Horizontal); 140 °(Vertical)
Best Viewing Distance	≥2.5m
Gray Grade	14 bits
Display Color	4.4 trillion colors
Brightness Adjustment	100 grades by software or automatically by sensor
Max. Power Consumption	24 W
Control System	
Frame Frequency	≥60Hz
Refresh Frequency	≥1920Hz
Input Signal	Composite Video, S-video, DVI, HDMI, SDI, HD-SDI
Control Distance	100m (Ethernet cable); 20KM (optical fiber cable)
Support VGA Mode	800*600, 1024*768, 1280*1024, 1600*1200
Color Temperature	5000—9300 adjustable

Brightness Correction	Pixel by pixel, module by module, cabinet by cabinet
<b>Reliability</b>	
Working Temperature	-20~+60 ℃
Storage Temperature	-30~+70 ℃
Working Humidity	10%~90% RH
Lifetime	100,000 hours
MTBF	5000 hours
Continuous Operating Time	≥72 hours
Protection Grade	IP31
Out-of-Control Pixel Rate	≤0.01%

**Package**





