



Product Model	EX2918MGX
Signal Type	Digital
Motor Type	High Speed Brushless Motor
Operating Voltage	DC 6V-8.4V (HV)
Operating Angle	180° ± 1°(14bit ENCODER)
Control System	PWM Control(1500 uSec in the central point)
Pulse Width	500 to 2500 uSec(Support SR/SSR/SUR/SFR)
Working Frequency	50-2000Hz
Dead Band	2uSec
Operating Temperature	-20°C ~ +70°C
Case Material	Full CNC Aluminum
Bearing	All Ball Bearings
Gear Material	Strength Stainless Steel Oblique Gears
Horn Gear Spial	Ø6.0-25T
Waterproof Level	IP67
Programmable	Programmable Angle Support 720 Degrees
CE FCC Certification	Yes
Connector Wire	22AWG 300mm JR Silicone Wire
Dimension	40x20x29mm(1.57 x 0.78 x 1.14in)
Weight	73g(2.57oz)

Operating Speed	Stall Torque
6.0V@ 0.04sec / 60°	12kg-cm (166.5 oz-in)4200mAh
7.4V@ 0.035sec / 60°	16kg-cm (222 oz-in)5500mAh
8.4V@ 0.03sec / 60°	18kg-cm (250 oz-in)6000mAh

