

LED High Bay Light

100W~240W





















Add: Room 803, Chevalier House, No 45-51 Chatham Road South, Tsim Sha Tsui. Hong Kong















Features:

- * Light Efficiency: 150lm/W;
- * High bright EVERLIGHT LEDs;
- * Optics of 60°/90°/120° available on request;
- * High-transmittance and anti-UV Polycarbonate lens;
- * Excellent thermal management design;
- * Die-casting aluminum with polyester powder coat finish;
- * IP65/IK08 rating for outdoor usage;
- * Hook hanging and U-bracket installation are available;
- * Energy savings, no UV and IR radiations, emits low heat;
- * 1-10V dimming for low power consumption;
- * DLC/ETL/cETL/SAA/C-TICK/FCC/CE/RoHS approval;
- * 5 years warranty



Specifications:


Model	RMS-L2204
Wattage	100W/150W/200W/240W
Luminous Flux	150LM/W
Beam Angle	60°/90°/120°
Color Temperature	3000K~6000K
Input Voltage	AC100-277V, 50-60Hz
LED Brand	Everlight
CRI	Ra>80
PF	>0.9
Life Hours	50,000
Operation Temperature	-35°C~55°C
IP Rating	IP65








Dimension:

Unit: mm









100W 150W 200W/240W













Details:



• High bright Everlight SMD2835. LM80 listed. Whole lamp is 150LPW



 MEANWELL/PHILIPS/ SOSEN/FAHOLD/ ROMANSO LED driver. 1-10V dimming, high reliable, offer 5 years warranty



• Die cast aluminum alloy body, cooling fins provide maximum heat dissipation.



 Die cast hook mount standard for ease of installation, surface mounted baracket optional.



 LED and heat sink are parallel, no dark area, no shadow.



 3 kinds of beam angle options to suit different lighting requirements in different areas.





• 60°/90° of PC/ Aluminum Reflectors are optional.



 Ip65 waterproof for wet location

Mounting Height & Equivalence:

100W 15,000 Lumens 15-20' Mounting Height **Equivalence** 175-250 HID 6-Lamp 32W T8





















Installation Instruction:

1. Hook hanging Installation





