

LED Work Light





KEY FEATURE

- Built-in switch to control on-off.
- Adjustable screw on the lamp, adjust lamp's angle by hand.
- Eliminates light bulb replacement and/or clean-up.
- Compact design utilizes aluminum housing for cooling system.
- High-visibility beam angles for optional.
- Cree LED is available.
- Over 50000 hours lifetime and offer 5 years warranty.
- ETL/cETL/CE/RoHS certificates.



20W/30W




50W/60W

SPECIFICATION

Item NO.	Watt	Total Lumens	Dimension	Beam Angle	LED Brand	CCT	Input Voltage	CRI	Power Factor	IP Rating
RMS-DL-20W	20W	2200LM±10%	Φ177*115.8mm	20°/30°/110°	CREE	3000K 4000K 5000K 5700K 6500K	AC100-277V, 50-60Hz	>70	>0.9	IP65
RMS-DL-30W	30W	3300LM±10%								
RMS-DL-50W	50W	5500LM±10%	Φ240*118.5mm	30°/80°/110°						
RMS-DL-60W	60W	6600LM±10%								

DETAILS

CREE



1/ BRANDED LED

Cree LED are available, LM80 report, long lifetime.



20° / 30° / 110°



30° / 80° / 110°

2/ BEAM ANGLES

High-visibility beam angles for optional:

20W /30W : 20°/30°/110°,
50W /60W : 30°/80°/110°.



3/ ALUMINUM HOUSING

Die-cast aluminum housing for maximum heat dissipation.



4/ REAR SWITCH BUTTON

Built-in switch to control on-off condition.



5/ STAINLESS STEEL CAGE

Better protection for light, anti-corrosion and durable.



6/ ELECTRICAL OUTLET

Come with regular male connector; 120V grounded plug is optional.



7/ BRACKET

Bracket mounted, easy installation



8/ ADJUSTABLE SCREW

Allow you to direct the light where you need it.

Multiple brackets and stands are optional

1



U-Stand



20W/30W



2



H-Stand with magnets



50W/60W



3



H-Stand without magnets



50W/60W




The bracket is adjustable for different lighting direction:



U-Stand for 20W/30W



H-Stand for 50W/60W



Strong Magnetic base prevents vibration from slipping.

- *Come with 10ft power cord with 120v grounded plug.
- *Portable handle, easy to carry and can tangle the cord up.
- *Built-in switch to control on-off condition.



Multiple brackets and stands are optional

4




5



Built-in switch to control on-off condition.

Bracket height is adjustable.
(Shortest height: 970mm/38.2"
Tallest height: 1910mm/75.2')



Quick-release system for detaching light from tripod.



2-in-1 waterproof connector+
10ft power cord with 120v
grounded plug.

Could be disassembled to use.

