

SP-650W



LED Grow Light

SP-650W LED grow light is designed for greenhouse supplemental lighting with linear lay out on top ceiling, long lifespan for its IP 67 waterproof and patented unibody heat-sink design, it perfectly matching with our wireless controller TSC-2 in centrally management.



FEATURES


- WiFi mesh technology, perfectly compatible with our wireless controller TSC-2, centrally management for large scale of greenhouse growing;
- IP 67 for long time working in damp environment;
- Patented unibody heat-sink design, greatly improves the heat dissipation capability;
- High and efficacy diodes make it spread powerful PPFD over 6FT×4FT grow area;
- Optimum full spectrum F1 for whole grow cycle;
- Slim and compact design contribute to a reduced shadow on plants, perfect for greenhouse supplemental lighting;
- Quick and Easy installation to save much time and laber cost;
- 5 Years warranty.

SPECIFICATIONS

| Model | SP-650W |
|---------------------------------|---------------------------------------------------------------|
| AC Input Power | 650 W |
| Efficacy | 2.8 μmol/J @ 277 V AC |
| Light Output PPF | 1820 μmol/s |
| Dimensions | 47.64" x 5.38" x 8.07" L - 1210 x W - 136.7 x H - 204.9 mm |
| Net Weight | 27.18 lb / 12.33 kg |
| Spectrum | F1 |
| AC Input Voltage | 120-277 V AC, 50/60 Hz |
| AC Current | 6.7 A (@ 120 V AC) 3.1 A (@ 240 V AC) 2.7 A (@ 277 V AC) |
| Power Factor | ≥ 0.9 |
| Thermal Management | Passive |
| Max. Ambient Temperature | 104 °F / 40 °C |
| Dimming | 0-10 V Dimmable |
| Total Harmonic Distortion (THD) | ≤ 25% |
| Lifespan Warranty | > 50,000 hours 5 Year Standard Warranty |
| Certificates | ETL, DLC, FCC, CE |

SPECTRUM

F1 Spectrum





CONTROL METHOD

We strongly encourage you to use our Master Controller TSC-2 for wireless or wired connection in large scale of growing, the Master Controller TSC-2 is an essential part for lighting and controlling the SP-650W. Press the silvery button under the power box 2 seconds for resetting.


Wireless Connection




Master Controller

TSC-2


Wired Connection




PPFD (PAR CHART)



SP-650W 5x5FT 36"/914 mm Height




SP-650W 5x5FT 48''/1219 mm Height




SP-650W 5x5FT 60"/1524 mm Height



PAR VALUE (µmol/m²/s)



DIMENSIONS & PACKAGING



CONTENTS

- A. 1 LED Grow Light
- B. 2 Stainless Steel Hanging Kits
- C. 1 Power Cord (6 ft / 180 cm)
- D. 1 Power Adapter
- E. 1 User Manual

| Model No. | SP-650W |
|---------------|---------------------------------------------------|
| Master carton | 51.38" x 7.48" x 10.83" L-1305 x W-190 x H-275 |
| G.W | 33.7 lbs / 15.3 kg |

