


LED Slim Adjustable Wall Pack Series

Wattages: 20W, 45W, 70W, 100W

LED Slim Adjustable Wall Pack series can be widely used in indoor or outdoor lighting (wet location). The head tilts from 0° to 90°. Ideal for mechanical or electronic processing workshops, storage warehouses, steel mills, gas stations, toll booth, waiting rooms, the platforms of railway station, indoor stadiums.



FEATURES

- Lumileds LED, high luminous efficiency and long working life.
- High efficiency LED Driver, the wide range input voltage AC120-277V/AC.
- Excellent optics design, greatly improve the light utilization and evenness.
- Cast Aluminum design, better cooling, light quality, LED T_j < 85°C.
- Photocell control available (Optional)
- 1-10V Dimming.

PHOTOCELL (SOLD SEPARATE)





JL-413C
Photoelectric Switch 120-277V

SPECIFICATION				
WATTAGE	WSD-SWP02W27-50K	WSD-SWP45W27-50K	WSD-SWP07W27-50K	WSD-SWP10W27-50K
LUMEN	2720 lm	5895 lm	9170 lm	13100 lm
EFFICACY	136 lm/W	131 lm/W	131 lm/W	131 lm/W
CCT	4000K, 5000K			
CRI	70			
INPUT VOLTAGE	120-277V			
POWER FACTOR	0.98			
DRIVER EFFICACY	90%			
DIMMING	1-10V Dimming			
LIGHT ANGLE	92°	86°	87°	89°
LIFE SPAN	75,000 hrs			
WORKING TEMPERATURE	-22°F ~ 113°F			
STORAGE TEMPERATURE	-40°F ~ 176°F			
OUTDOOR RATING	IP65			
CABLE	Input Connect, No cable			
WARRANTY	5 year limited			


LED Slim Adjustable Wall Pack Series

Wattages: 20W, 45W, 70W, 100W



DIMENSION



WATTAGE	WSD-SWP-02W27 WSD-SWP-45W27
NT. WEIGHT	2.9 lbs / 3.4 lbs
BOX DIM.	10" x 7.87" x 5.7"



WATTAGE	WSD-SWP-07W27
NT. WEIGHT	5 lbs
BOX DIM.	12.9" x 10.23" x 5.9"



WATTAGE	WSD-SWP-10W27
NT. WEIGHT	7.3 lbs
BOX DIM.	14.9" x 11.8" x 7"

ORDERING INFORMATION

EXAMPLE:

WSD-SWP-02W27-50K-D-P

WSD	SWP	02W	27	50K	D	P
COMPANY	PRODUCT	WATTAGE	VOLTAGE	CCT	FINISH	CONTROL
WSD LED INC	SWP Slim Adjustable Wall Pack	02W - (20W) 45W - (45W) 07W - (70W) 10W - (100W)	27 (AC120-277V)	40K - (4000K) 50K - (5000K)	D - (Dark Bronze) W - (White) B - (Black) S - (Silver)	P - (Photocell)

LED Slim Adjustable Wall Pack Series



Wattages: 20W, 45W, 70W, 100W

PHOTOMETRICS


For complete IES files, please visit our website.

WSD-SWP-02W27-50K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM





ISOLUX DIAGRAM




WSD-SWP-45W27-50K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM





ISOLUX DIAGRAM




WSD-SWP-07W27-50K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



ISOLUX DIAGRAM



LED Slim Adjustable Wall Pack Series


Wattages: 20W, 45W, 70W, 100W

PHOTOMETRICS


For complete IES files, please visit our website.

WSD-SWP-10W27-50K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE(50%):88.5 DEG



ISOLUX DIAGRAM

