


Wireless camera

Interface description


This manual is suitable for various types of cameras.

(The appearance may be different due to different batches. The details are subject to the receipt. This manual is only for the installation instructions of this series of equipment.)


1. Wireless Pan-tilt IP Camera



2. WiFi Spot Light Camera



3. WiFi MINI Dome Camera



Description

- 1. Photosensitive** Collect ambient luminosity value, turn on the infrared light when the current illuminance is less than 3 Lux.
- 2. Reset button** The working state of the device, long press 3-5 seconds to restore the factory, the camera will have a voice prompt broadcast.
- 3. SD card slot** TF card, storage video and playback video.
- 4. DC power supply** Power input
- 5. Network port and indicator light** Connect the Lan cable and check the current device status indicator light (flashes once /1 s on hotspot mode)

Software Installation

APP Download and Installation

Users can search "EseeCloud(IP Pro, VR Cam)" on APP store or Google Play, or scan the QR code below to install the APP.




Note: For iOS system, it requires iOS 9.0 version or above. For Android, Android 5.1 or above.

Account login


Account login: On the login interface, enter the account/ phone number/email, and the corresponding password, and click the "OK" button to log in.

Third-party login: APP supports third-party login. Click the third-party social software icon, jump to the APP to complete the authorization and log in.




Camera adding process description


1. Open the "EseeCloud" APP and click the "+" icon in the middle of the interface to enter the scan QR code interface;




2. Scan the QR code on the device and wait for the device indicator to flash and proceed to the next step;



3. On the Add device interface, click "Add";




5. To view and use via WiFi or other networks, please select **Remote View**; If there is no network, if you connect to the camera at close range, please select **Direct Connection**;



Remote View adding process


1. Select "Remote View" to add, connect the device to WiFi, select the working WiFi that the device needs to connect to, enter the password, and click Next;



2. Use the device to scan the QR code of the mobile phone according to the operation shown in the figure, and proceed to the next step after hearing the prompt tone or the device indicator light no longer flashes;




3. After the network configuration is successful, the device name can be added successfully.




Before operating this unit, please read these instructions carefully, and save them for future use.

Local direct connection add

1. Click "Direct Connection", set a password for the WiFi of the device, and enter the next step; (Direct connection can only be connected to the camera for viewing locally);




3. According to the interface guide, after connecting the device with its own WiFi, return to the APP;



2. Use the device to scan the QR code of the mobile phone according to the operation shown in the figure, and go to the next step after hearing the prompt tone or the device indicator light no longer flashes;



4. The device is successfully added, please set a name for the device.




Note: the local direct connection needs to maintain a WiFi connection with the device to properly preview the device screen.

When the QR code of the device cannot be found (or the scan code is unsuccessful):

1. Connect to the IPCXXX hotspot in the phone settings, the password is 11111111;






2. Click "Other ways to add" in the code scan interface, and select the "Standalone camera".




Remote View adding process


1. Select "Remote View" to add, connect the device to WiFi, select the working WiFi that the device needs to connect to, enter the password, and click Next;




3. To view and use via WiFi or other networks, please select "Remote View"; if there is no network, to view the camera at close range, please select "Direct Connection";



2. Please wait patiently during the device configuration network;



3. The device is successfully added, please set a name for the device.




Wired add configuration process

Power on the device, connect it to a router with internet access with a network cable.

1. Scan the QR code of the device, and click "Add";



2. After setting the name for the device, it can be added successfully.



Warning




In case of fire or lightning, pls don't put product in damp and raining place, operate or maintain according to the user manual.



Be careful when you see attachment with a Dangerous Voltage which might cause serious electric accident.



Warning To reduce electric shock, unprofessional people please don't open product front panel or rear panel



Warning In case of electric shock and fire, pls don't use power supply beyond power list in user manual

Notice:

1. Ensure your equity, pls read the user manual carefully before you use the product
2. Pls contact professional people if you need install and maintain the product
3. Working Environment: temperature of -20°C~+60°C, relative humidity under 85%
4. Pls don't exceed the user manual's standard range of temperature, humidity and voltage.