LEDSION

LED CCT & Wattage Tunable Ceiling Flush Mount Light

Product Description

LEDSION CCT & Wattage Tunable 14IN Ceiling light use best die-casting aluminum+PC housing, anti-corrosion painting design. High-performance

Replace 12-45W MH/HPS.

Advantage

- > ETL approved.
- Input voltage 120VAC.
- No UV or IR in the beam.
- > Easy to install and operate.
- Energy saving, long lifespan.

Light is soft and uniform, safe to eyes.

- > Instant start, NO flickering, NO humming.
- Green and eco-friendly without mercury.



Applications

Bedroom, dining room, hallway, kitchen, entry, foyers, restroom, closet, attic, basement, garage, utility room, or office areas.



Bedroom



Dinning Room



Hallway



Living Room





http://www.ledsion.com FREE: 1-972-951-7795 E-mail: info@ledsion.com

Add: 4940 Top Line Dr, Dallas, TX 75247


LED CCT & Wattage Tunable Ceiling Flush Mount Light

Specifications

LED SION

Model No.	LS-CM44B	
Input Power	6W/10W/15W	
Lumen	1350-1800LM	
Lumen Efficacy	95-120LM/W	
Color Temperature	3000K, 4000K, 5000K	
CRI	>80	
Viewing Angle	120 Degree	
Input Voltage	120VAC 50/60Hz	
PF	≥0.9	
THD	≤20%	
Driver Brand	China brand driver	
LED Brand	Samsung	
LED Type	2835	
LED QTY	48 PCS	
Dimmer	/	
Housing	Aluminum Alloy+PC	
Housing Color	White	
Waterproof Rating	IP20	
Operating Temperature	-20°C TO 40°C	
Operating Humidity	20%-90% RH	
Storage Temperature	-40°C TO 80°C	
Storage Humidity	10%-90% RH	
Warranty Time	5 Years	

Photometrics




http://www.ledsion.com FREE: 1-972-951-7795 E-mail: info@ledsion.com

Add: 4940 Top Line Dr, Dallas, TX 75247

LED CCT & Wattage Tunable Ceiling Flush Mount Light

Dimensions

LED SION



Model	Diameter	Height
LS-CM44B	Ø350±3	Ø76.5±2

Notice for User

Please turn off power before install or change assembly parts.

The input voltage and lamps should be matched, after connecting the power line,

Please make sure the wiring section is insulated.

No-professionals, must not install and disassemble the lamps.

After-sale Service

The product refers to electrics knowledge. Please don't disassemble it by yourself.

If any quality problem happens, please contact the factory for warranty details.

NOTE: Actual performance may differ as a result of end-user environment and application. All values are without notice.

http://www.ledsion.com FREE: 1-972-951-7795 E-mail: info@ledsion.com

Add: 4940 Top Line Dr, Dallas, TX 75247