



Rio PRO 360™

Faster, flexible, professional direct-to-card printing



FEATURES

- High speed and capacity
- 300 dpi color dye sublimation, monochrome, thermal rewritable
- Manual and hopper fed
- Single-sided or double-sided printing
- 200 full color cards per hour
- 200 card input / 30 card output
- 10x custom Holokote designs


SPECIFICATIONS

Print mode	Colour dye sublimation, monochrome thermal printing and rewritable technology.
Card security	A Holokote security watermark can be printed across the card surface. With the Rio Pro 360, this watermark can be customised to an organisation's logo, or some other unique security design. LYNK enables the secure online delivery of up to ten bespoke Holokotes® to the printer through the driver interface. When used with HoloPatch® cards, one area of the Holokote® watermark can be highlighted as a high visibility security seal.
Encoding security options	Magnetic stripe encoding: HiCo and LoCo ISO 7811, JIS2. Smart card encoding: Contact chip, MIFARE®, DESFire® and iClass®. Others available.
Printer interfaces	High Speed USB 2.0, USB 3.0 compatible - Type B, 10/100 Ethernet. 2x internal USB 2.0 (one host) - Type A.
Driver compatibility	Windows XP, Vista, 7, 8, 10 (32 and 64bit) Windows server 2003 R2 SP2, 2008, 2012, 2016. Mac OS X 10.9.0 upwards. Linux with CUPS support
Card capacity	100 card feeder, 70-card stacker.
Weight	4.7kg /10.4 lbs.
Power source	External power supply 100-240V 50-60Hz autoranging.
Dimensions	470mm L x 220mm W x 300mm H / 18.5" L x 8.6" W x 12" H including feeder and stacker.
Operating environment	Sheltered office environment 10°C to 30°C / 50°F to 85°F.

Standard Features



Optional Features



The intelligent identity solution for:

Enterprise, facilities, education, governments and payment applications.