

PE series PCB safety isolation transformer



Model:PE3022-M

Characteristics:

1. Vacuum epoxy sealing, 100 °C/6 hours high temperature aging, life span of 20 years, high electrical strength
2. High quality H18 silicon steel sheet, low temperature rise, high efficiency
3. PBT engineering plastic, environmental protection, flame retardant, 120 degrees no deformation
4. Reasonable structure, convenient installation, low noise, strong seismic, sealed waterproof, moisture-proof



Technical Index:

Technical Index: PCB

Flame resistance : UL94-V0

Insulation class: B

Operation temperature: -30°C ~ +70°C

Work frequency: 50Hz~60Hz


Dielectric strength: Pri./Sec. 3.75KV 50Hz 1min 5mA, Sec./Sec 500V 50Hz 1min 5mA

Technical Parameters table:

Primary voltage	110/220/230/380	V
Primary voltage range	±10	%
Voltage regulation	≤30	%
Power	3.4	VA
Temperature rising	≤20	°C
No load loss	≤0.7	W
weight	130	g

Secondary voltage		Secondary no load voltage		Secondary full load current	
Single	Double	Single	Double	Single	Double
6V	6V×2	8.6V	8.6V×2	566mA	283mA×2
7.5V	7.5V×2	10.7V	10.7V×2	453mA	226mA×2
9V	9V×2	12.9V	12.9V×2	377mA	188mA×2
12V	12V×2	17V	17V×2	283mA	141mA×2
15V	15V×2	21.4V	21.4V×2	226mA	113mA×2
18V	18V×2	25.7V	25.7V×2	188mA	94mA×2
24V	24V×2	34V	34V×2	142mA	71mA×2

Schematic Diagram:



Dimension (in mm) :

