

## Model:PE4110C-I

### Characteristics:

1. Vacuum epoxy sealing, 100 °C/6 hours high temperature aging, life span of 20 years, high electrical strength
2. High quality Z11 silicon steel sheet, low temperature rise, high efficiency
3. PBT engineering plastic, environmental protection, flame retardant, 120 degrees no deformation
4. Reasonable structure, convenient installation, low noise, strong seismic, sealed waterproof, moisture-proof



### Technical Index:

Technical Index: PCB

Flame resistance : UL94-V0

Insulation class: B

Operation temperature: -30°C ~ +70°C

Work frequency: 50Hz~60Hz


Dielectric strength: Pri./Sec. 3.75KV 50Hz 1min 5mA, Sec/Sec 500V 50Hz 1min 5mA

### Technical Parameters table:

Primary voltage	110/220/230/380	V
Primary voltage range	±10	%
Voltage regulation	≤30	%
Power	3	VA
Temperature rising	≤21	°C
No load loss	≤0.3	W
weight	130	g

Secondary voltage		Secondary no load voltage		Secondary full load current	
Single	Double	Single	Double	Single	Double
6V	6V×2	8.1V	8.1V×2	416mA	208mA×2
7.5V	7.5V×2	10.7V	10.7V×2	333mA	166.5mA×2
9V	9V×2	12.8V	12.8V×2	277mA	138.5mA×2
12V	12V×2	17.1V	17.1V×2	208mA	104mA×2
15V	15V×2	21V	21V×2	166mA	83mA×2
18V	18V×2	25.7V	25.7V×2	138mA	69mA×2
24V	24V×2	34.2V	34.2V×2	104mA	52mA×2

### Schematic Diagram:



Dimension (in mm±0.5) :

