

Model:PE4809C-M

Characteristics:

1. Vacuum epoxy sealing, 100 °C/6 hours high temperature aging, life span of 20 years, high electrical strength
2. High quality H18 silicon steel sheet, low temperature rise, high efficiency
3. PBT engineering plastic, environmental protection, flame retardant, 120 degrees no deformation
4. Reasonable structure, convenient installation, low noise, strong seismic, sealed waterproof, moisture-proof



Technical Index:

Technical Index: PCB

Flame resistance : UL94-V0

Insulation class: B

Operation temperature: -30°C ~ +70°C

Work frequency: 50Hz ~ 60Hz


Dielectric strength: Pri./Sec. 3.75KV 50Hz 1min 5mA, Sec/Sec 500V 50Hz 1min 5mA

Technical Parameters table:


Primary voltage	110/220/230/380	V
Primary voltage range	±10	%
Voltage regulation	≤25	%
Power	4	VA
Temperature rising	≤16	°C
No load loss	≤0.82	W
weight	160	g

Secondary voltage		Secondary no load voltage		Secondary full load current	
Single	Double	Single	Double	Single	Double
6V	2×6V	8V	2×8V	667mA	2×333mA
7.5V	2×7.5V	10V	2×10V	533mA	2×267mA
9V	2×9V	12V	2×12V	444mA	2×222mA
12V	2×12V	16V	2×16V	333mA	2×167mA
15V	2×15V	20V	2×20V	267mA	2×133mA
18V	2×18V	24V	2×24V	222mA	2×111mA
24V	2×24V	32V	2×32V	167mA	2×83mA


Schematic Diagram:



Dimension (in mm±0.5) :



Side View



Bottom View