

Φ23mm Aperture Split core current transformer



Product features

- Secure locking buckle, easy to install
- Lead wire type output
- the length can be customized
- Suspended mounting

Product application

- Portable instrument
- Household metering
- Monitoring the load of machine


Product advantage

- Small volume,
- Low cost
- High turns, High precision

Installation diagram

Primary threading method

Firing line





Typical technical index:

- Material of core——Silicon steel sheet
- Working voltage——Phase voltage $\leq 720\text{V}$
- Working temperature—— $-30^{\circ}\text{C} \sim +65^{\circ}\text{C}$
- Storage temperature—— $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- Frequency range—— $50\text{Hz} \sim 60\text{Hz}$
- Dielectric strength——Input (bare conductor) /output AC 800V/1min 5mA 50Hz
Output/Outer shell AC 3.5KV/1min 5mA 50Hz)

- Weight———103g

Electrical parameters The following parameters are typical values. The actual values shall be subject to the actual measurement of the product)

Model	Input current	Output current	turns ratio	Accuracy	sampling resistance	Lead specification/schematic diagram
SCT023R	100A	50mA	1:2000	0.5%	50 Ω	Leading wire specification: AWG22 0.3mm² Black and white twisted pair lead length: 145cm~150cm  TVS: Transient voltage suppressor current output type. the secondary is not allowed to open.
SCT023R	100A	80mA	1:1250	0.5%	20 Ω	
SCT023R	100A	100mA	1:1000	0.5%	10 Ω	
SCT023R	200A	50mA	1:4000	0.5%	80 Ω	
SCT023R	200A	80mA	1:2500	0.5%	30 Ω	
SCT023R	200A	100mA	1:2000	0.5%	20 Ω	
SCT023R	300A	50mA	1:6000	0.5%	80 Ω	
SCT023R	300A	80mA	1:3750	0.5%	30 Ω	
SCT023R	300A	100mA	1:3000	0.5%	20 Ω	
SCT023R	400A	50mA	1:8000	0.5%	100 Ω	
SCT023R	400A	80mA	1:5000	0.5%	40 Ω	
SCT023R	400A	100mA	1:4000	0.5%	25 Ω	

Model	Input current	Output voltage	Accuracy	Load impedance	Lead specification/schematic diagram
SCT023R	50A	0.333V	0.5%/1%	$\geq 10K \Omega$	 Voltage output type : Built-in with sampling resistance Voltage output type : not allowed secondary short circuit. AWG22(0.3mm²) black and white twisted pair, leads to 1.48m
SCT023R	100A	0.333V	0.5%/1%	$\geq 10K \Omega$	
SCT023R	200A	0.333V	0.5%/1%	$\geq 10K \Omega$	
SCT023R	300A	0.333V	0.5%/1%	$\geq 10K \Omega$	
SCT023R	400A	0.333V	0.5%/1%	$\geq 10K \Omega$	
SCT023R	600A	0.333V	0.5%/1%	$\geq 10K \Omega$	

statement:

As our products are constantly being improved and updated, we reserve the right to modify the content of this specification at any time without prior notice.

Dimensions: (in:mm±0.5)

