

TA22 Through core type precision current transformer



Characteristics:

Epoxy resin encapsulated, Nanocrystalline core, mini outline size, fully enclosed. Electrical load remote monitoring, as the input signal of electric control system, lack of phase indicating, electrical energy measuring, motor monitoring.

Technical index:

Mounting type: Plate installation
 Material of the core: Nanocrystalline
 Flame resistance: UL94-V0
 Execution standard: GB20840-2014
 Operating temperature: $-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$
 Storage temperature: $-30^{\circ}\text{C} \sim +80^{\circ}\text{C}$
 Frequency range: 20Hz-20KHz
 Dielectric strength: 3.5KV 50Hz 1min


Product picture : (the printed words are for reference only, subject to the actual product)



Electrical parameters: (The following parameters are typical values and actual values will be subject to product testing)

| Model | TA22-100 | TA22-200 | TA22-300 | Unit |
|---------------------|------------|------------|------------|----------|
| Rated input | 80 | 100 | 150 | A |
| Rated output | 80 | 50 | 50 | mA |
| Turns ratio | 1: 1000 | 1: 2000 | 1: 3000 | |
| Linearity | ≤ 0.2 | ≤ 0.2 | ≤ 0.2 | % |
| Sampling resistance | 50 | 100 | 200 | Ω |
| Weight | 76 | 76 | 76 | g |

Schematic diagram:



current output type.
 the secondary is not allowed to open.

Dimensions (in mm ± 0.5) :

