

TV6023BK



Characteristics:

1. Vacuum epoxy potting, 100 °C/6 h high temperature aging, Twenty years of life, High electrical strength
2. High quality silicon steel sheet, Low temperature, High efficiency
3. PBT engineering plastic, environmental protection, flame retardant, 120 degrees without deformation
4. Reasonable structure, Easy installation, Low noise, Strong earthquake sealed waterproof, moistureproof

Technical Index:

- Technical Index: Din-rail type mounting
- Flame resistance: UL94-V0
- Insulation class: B
- Operation temperature: -30 °C ~ +70 °C
- Work frequency: 50Hz ~ 60Hz
- Dielectric strength: Primary/secondary (highest) 5KV 50Hz 1min 5mA


Product picture print for reference only, subject to the actual product



Electrical parameters: The following parameters are typical values. The actual values shall be subject to the actual measurement of the product

Primary voltage	110V	220V	230V	380V	400V	500V	660V	Unit
Secondary voltage	5/10/100							V
Accuracy	0.5/1							%
Power	0.5/1							VA
Weight	695							g
Dielectric strength	5							KV

Schematic Diagram:



Noted

- ① Standard output is 5 v / 10 v / 100 v three choose one
- ② 0.5% accuracy corresponds to 0.5VA output power, 1% accuracy corresponds to 1VA output power

Dimensions (in mm±0.5)

